

TECHNICAL DATASHEET

APC • SERVER RACKS

APC NetShelter 6U low-profile wall-mount cabinet, server depth, 230 V fan, black

6U low-profile wall-mount cabinet, 762 mm equipment depth, 230 V fan

SKU AR106VI

6U

APC



HEIGHT IN U

6U

EXTERNAL DIMENSIONS

648 × 353 × 968 mm

MANUFACTURER

APC by Schneider Electric

PRICE

On request**REQUEST A QUOTATION ONLINE**serverinvest.com/product/apc-ar106vi

01 Product overview

The APC AR106VI is a 6U low-profile NetShelter enclosure that mounts deep rack equipment flat against a wall. Instead of projecting far into the room like a traditional wall cabinet, it holds devices in a vertical orientation, so servers and UPS units up to 762 mm deep can be installed in corridors, back offices or retail spaces with minimal intrusion.

The cabinet measures 648 × 353 × 968 mm (H × W × D) according to the Schneider Electric datasheet and supports 113.4 kg static and dynamic load. A built-in 230 V fan provides active ventilation, and the perforated door protects the equipment while allowing airflow.

It is well suited to edge deployments that combine an APC Smart-UPS, NetBotz physical and environmental monitoring and EcoStruxure IT cloud-based management in one compact, wall-mounted package.

UL 2416 listed, IP20; 5-year warranty.

HIGHLIGHTS

- 6U 19" low-profile wall-mount enclosure for deep equipment
- Equipment mounting depth 762 mm
- 113.4 kg static and dynamic load
- Integrated 230 V fan ventilation, perforated door
- UL 2416, IP20, 5-year warranty

KEY SPECIFICATIONS

Manufacturer	APC by Schneider Electric
Model	AR106VI
Series	NetShelter Wall-mount Low-Profile
EAN	0731304402015
Height in U	6U
External dimensions (H × W × D)	648 × 353 × 968 mm
Usable equipment depth	up to 762 mm
Unit weight	36.3 kg
Mounting rails	19" EIA-310 mounting rails
Static load rating	113.4 kg
Dynamic load rating	113.4 kg
Ventilation	Built-in fan, 230 V



02 Full specifications

GENERAL

Manufacturer	APC by Schneider Electric
Model	AR106VI
Series	NetShelter Wall-mount Low-Profile
EAN	0731304402015

DIMENSIONS

Height in U	6U
External dimensions (H × W × D)	648 × 353 × 968 mm
Usable equipment depth	up to 762 mm
Unit weight	36.3 kg

MOUNTING

Mounting rails	19" EIA-310 mounting rails
----------------	----------------------------

LOAD

Static load rating	113.4 kg
Dynamic load rating	113.4 kg

CONSTRUCTION

Ventilation	Built-in fan, 230 V
Colour	Black

DOORS & PANELS

Front door	Perforated
------------	------------

COMPLIANCE

IP rating	IP20
Standards	UL 2416

WARRANTY

Warranty	60 months (5 years)
----------	---------------------

03 Engineered, delivered & supported by ServerInvest

Engineering & sizing

Selected and sized against your real IT load, room and redundancy targets.

Installation

Delivery, installation and commissioning by our engineers across Europe.

Certified processes

ISO 9001, ISO 14001 and ISO 27001 certified project delivery.

Service & support

Maintenance, spare parts and support from a single partner.



Interested in this solution?

Request a quotation online or talk to a solutions engineer — we reply within one business day.
office@serverinvest.com

