

TECHNICAL DATASHEET

APC • SERVER RACKS

APC NetShelter 12U wall-mount cabinet, UPS depth, side-mount, black

12U UPS-depth wall-mount cabinet, 835 mm mounting depth, 158 kg load

SKU AR112SM

12U

APC



HEIGHT IN U

12U

EXTERNAL DIMENSIONS

**662 × 600 × 1037
mm**

MANUFACTURER

APC by Schneider Electric

PRICE

On request**REQUEST A QUOTATION ONLINE**serverinvest.com/product/apc-ar112sm

01 Product overview

The APC AR112SM is a 12U NetShelter UPS-depth wall-mount enclosure designed to put full-depth single-phase equipment - APC Smart-UPS and Easy UPS models or rack servers - onto a wall. It provides up to 835 mm of mounting depth, yet the side-mounted design keeps the cabinet projecting less than 25 inches (about 635 mm) from the wall. Overall dimensions are 662 mm high, 600 mm wide and 1037 mm deep.

Bracket-style wall mounting makes installation quick and safe, and equipment can be installed and configured before the cabinet is hung. Top and bottom cable openings with rear cable channels keep wiring organised, and vertical mounting space accepts a Zero-U PDU without using rack units.

The pre-assembled steel enclosure supports 158 kg (350 lb), has a perforated door for passive ventilation and is rated IP2X. It is designed to help secure sensitive data in PCI-scoped environments and works with APC NetBotz for access control, video surveillance and environmental monitoring (sold separately).

UL 2416 listed (UL/cUL); 5-year warranty.

KEY SPECIFICATIONS

Manufacturer	APC by Schneider Electric
Model	AR112SM
Series	NetShelter Wall-mount UPS-Depth
EAN	0731304632641
Height in U	12U
External dimensions (H × W × D)	662 × 600 × 1037 mm
Usable equipment depth	190–835 mm
Unit weight	58.9 kg
Mounting rails	19" EIA-310 mounting rails
OU accessory mounting	Vertical Zero-U PDU mounting space
Static load rating	158 kg
Front door	Perforated

HIGHLIGHTS

- 12U wall-mount cabinet with 835 mm mounting depth for UPS and servers
- Side-mount profile projects < 25 in (≈635 mm) from the wall
- 158 kg (350 lb) static load
- Top/bottom cable openings, Zero-U PDU space
- Pre-assembled, bracket-style mounting, perforated door
- UL 2416, 5-year warranty



02 Full specifications

GENERAL

Manufacturer	APC by Schneider Electric
Model	AR112SM
Series	NetShelter Wall-mount UPS-Depth
EAN	0731304632641

DIMENSIONS

Height in U	12U
External dimensions (H × W × D)	662 × 600 × 1037 mm
Usable equipment depth	190–835 mm
Unit weight	58.9 kg

MOUNTING

Mounting rails	19" EIA-310 mounting rails
OU accessory mounting	Vertical Zero-U PDU mounting space

LOAD

Static load rating	158 kg
--------------------	--------

DOORS & PANELS

Front door	Perforated
------------	------------

CONSTRUCTION

Mounting	Side-mounted, bracket-style wall mounting
Ventilation	Passive
Cable entry	Top and bottom openings, rear cable channels
Assembly	Pre-assembled
Colour	Black
Material	Steel

COMPLIANCE

IP rating	IP2X
Standards	UL 2416
Certifications	UL/cUL listed

WARRANTY

Warranty	60 months (5 years)
----------	---------------------

03 Engineered, delivered & supported by ServerInvest

Engineering & sizing

Selected and sized against your real IT load, room and redundancy targets.

Installation

Delivery, installation and commissioning by our engineers across Europe.

Certified processes

ISO 9001, ISO 14001 and ISO 27001 certified project delivery.

Service & support

Maintenance, spare parts and support from a single partner.



Interested in this solution?

Request a quotation online or talk to a solutions engineer — we reply within one business day.
office@serverinvest.com

