TECHNICAL DATASHEET

APC · SERVER RACKS

APC NetShelter SV 42U 600 mm × 1060 mm server rack enclosure, with sides, black

42U essential server enclosure, 600 × 1060 × 2057 mm, 1000.2 kg static load

SKU AR2400 | 42U | APC



HEIGHT IN U	EXTERNAL DIMENSIONS	MANUFACTURER	PRICE
42U	2057 × 600 × 1060 mm	APC by Schneider Electric	On request

REQUEST A QUOTATION ONLINE
serverinvest.com/product/apc-ar2400

01 Product overview

The APC AR2400 is a NetShelter SV enclosure, Schneider Electric's essential-class rack for low- and medium-density server and networking applications. It provides 42U of 19-inch EIA-310 space in a 600 mm wide, 1060 mm deep cabinet with an external height of 2057 mm. Its 600 mm width matches standard data-centre floor tiles for dense row layouts.

The frame is rated for 1000.2 kg static and 459.9 kg dynamic load. Vertical mounting rails can be set at fixed adjustment points for equipment from 167.6 mm up to 777.2 mm deep, and four rear accessory brackets accept rack PDUs and cable organisers. Cable access is provided through both the roof and the rack bottom.

A perforated front door and perforated split rear doors deliver front-to-back ventilation and need little clearance behind the rack. The front door can be moved to the other side or swapped with the rear doors, and doors lift off on spring-loaded hinge pins. Lockable full-height side panels and doors are keyed alike. Casters, levelling feet and four bolt-down brackets are included.

NetShelter SV racks comply with EIA-310-E and are listed to UL 2416; the AR2400 is covered by a 5-year warranty.

KEY SPECIFICATIONS

Manufacturer	**APC by Schneider Electric**
Model	**AR2400**
Series	**NetShelter SV**
Height in U	**42U**
External dimensions (H × W × D)	**2057 × 600 × 1060 mm**
Usable equipment depth	**167.6–777.2 mm**
Unit weight	**112.2 kg**
Mounting rails	**19" EIA-310 mounting rails**
Rail depth adjustment	**Fixed adjustment points**
0U accessory mounting	**4 rear accessory brackets**
Static load rating	**1000.2 kg**
Dynamic load rating	**459.9 kg**

HIGHLIGHTS

- 42U EIA-310 19" space, 600 × 1060 mm footprint, 2057 mm tall
- 1000.2 kg static / 459.9 kg dynamic load
- Equipment depth 167.6–777.2 mm, 4 rear accessory brackets
- Perforated front door and split rear doors, lockable side panels
- Casters, levelling feet and bolt-down brackets included
- 5-year warranty

02 Full specifications

GENERAL	
Manufacturer	APC by Schneider Electric
Model	AR2400
Series	NetShelter SV

DIMENSIONS	
Height in U	42U

External dimensions (H × W × D)	2057 × 600 × 1060 mm
Usable equipment depth	167.6–777.2 mm
Unit weight	112.2 kg

MOUNTING

Mounting rails	19" EIA-310 mounting rails
Rail depth adjustment	Fixed adjustment points
0U accessory mounting	4 rear accessory brackets

LOAD

Static load rating	1000.2 kg
Dynamic load rating	459.9 kg

DOORS & PANELS

Front door	Perforated, reversible/interchangeable
Rear door	Perforated split doors
Side panels	Single full-height, lockable

CONSTRUCTION

Cable entry	Roof and rack bottom
Baying	Baying hardware included
Casters / feet	Pre-installed casters, levelling feet, 4 bolt-down brackets
Colour	Black
Material	Steel; 14 gauge EIA mounting rail, 16 gauge front door, 18 gauge post, 16 gauge rear door, 19 gauge roof, 18 gauge side panels

COMPLIANCE

Standards	UL 2416, UL 60950-1, EIA-310E

PACKAGE

Package contents	Baying hardware, Doors, Key(s), Keyed-alike doors and side panels, Leveling feet, Mounting Hardware, Pre-installed casters, 4 x Bolt down brackets, Roof, Side Panels

WARRANTY

Warranty	60 months (5 years)

03 Engineered, delivered & supported by ServerInvest

Engineering & sizing
Selected and sized against your real IT load, room and redundancy targets.

Installation
Delivery, installation and commissioning by our engineers across Europe.

Certified processes
ISO 9001, ISO 14001 and ISO 27001 certified project delivery.

Service & support
Maintenance, spare parts and support from a single partner.

NATCERT ISO 9001 · NATCERT ISO 14001 · NATCERT ISO 27001 · CISCO · tp-link · Omada by tp-link

Interested in this solution?

Request a quotation online or talk to a solutions engineer — we reply within one business day.
office@serverinvest.com