TECHNICAL DATASHEET

APC · SERVER RACKS

APC NetShelter SX Gen 2 52U 600 mm × 1200 mm server rack, with sides, white

52U server enclosure, 600 × 1200 × 2436 mm, 1701 kg static load

SKU AR3308W2 | 52U | APC

HEIGHT IN U	EXTERNAL DIMENSIONS	MANUFACTURER	PRICE
52U	2436 × 600 × 1200 mm	APC by Schneider Electric	On request

REQUEST A QUOTATION ONLINE
serverinvest.com/product/apc-ar3308w2

01 Product overview

The APC AR3308W2 belongs to the second generation of Schneider Electric's NetShelter SX family, the company's premium 19-inch enclosure line for data centres, server rooms and edge sites. It provides 52U of EIA-310 mounting space in a 600 mm wide, 1200 mm deep frame that stands 2436 mm tall, a depth that comfortably houses modern long-chassis servers and storage with room left for rear cabling and PDUs.

The welded steel frame is rated for 1701 kg static and 1020.6 kg dynamic (rolling) load, and the 19-inch EIA mounting rails adjust in 6 mm increments, accepting equipment from 190.5 mm to 1048 mm deep. 2 full-height 0U accessory channels at the rear take vertical rack PDUs and cable managers without consuming rack units. The roof offers five large cable entry points (three front, two rear) and can be removed without tools.

The curved, reversible front door and the flat rear doors are 80% perforated for front-to-back airflow and swing up to 270° (180° when bayed). Split, lockable side panels and 3-point key locking secure the installation, and doors and side panels are keyed alike. Casters and levelling feet are factory-fitted, and baying hardware is included for building rows.

NetShelter SX Gen 2 enclosures are UL listed, RoHS and REACH compliant, and backed by a 5-year Schneider Electric warranty.

KEY SPECIFICATIONS

Manufacturer	**APC by Schneider Electric**
Model	**AR3308W2**
Series	**NetShelter SX Gen 2**
Height in U	**52U**
External dimensions (H × W × D)	**2436 × 600 × 1200 mm**
Usable equipment depth	**190.5–1048 mm**
Unit weight	**168.6 kg**
Mounting rails	**19" EIA-310 mounting rails**
Rail depth adjustment	**6 mm (0.25 in) increments**
0U accessory mounting	**2 full-height rear 0U accessory channels**
Static load rating	**1701 kg**
Dynamic load rating	**1020.6 kg**

HIGHLIGHTS

- 52U EIA-310 19" space, 600 × 1200 mm footprint, 2436 mm tall
- 1701 kg static / 1020.6 kg dynamic load rating
- Rails adjust in 6 mm steps, equipment depth 190.5–1048 mm
- 80% perforated curved front door and rear doors, 3-point locking
- 2 full-height rear 0U accessory channels, toolless roof with 5 cable entries
- 5-year warranty, UL / RoHS / REACH

02 Full specifications

GENERAL	
Manufacturer	APC by Schneider Electric
Model	AR3308W2
Series	NetShelter SX Gen 2

DIMENSIONS	
Height in U	52U
External dimensions (H × W × D)	2436 × 600 × 1200 mm
Usable equipment depth	190.5–1048 mm
Unit weight	168.6 kg

MOUNTING

Mounting rails	19" EIA-310 mounting rails
Rail depth adjustment	6 mm (0.25 in) increments
0U accessory mounting	2 full-height rear 0U accessory channels

LOAD

Static load rating	1701 kg
Dynamic load rating	1020.6 kg

DOORS & PANELS

Front door	Single curved perforated door, reversible, 270° swing (180° bayed)
Rear door	Perforated, flat, 270° swing
Door perforation	80%
Lock	3-point locking, key-locking handles
Side panels	Split, lockable

CONSTRUCTION

Cable entry	Toolless roof with 5 large cable entry points (3 front, 2 rear); bottom plate optional
Baying	Baying kit included
Casters / feet	Casters and levelling feet included
Colour	White
Material	Steel; 14 gauge EIA mounting rail, 16 gauge front door, 16 gauge post, 18 gauge rear door, 18 gauge roof, 18 gauge side panels

COMPLIANCE

Certifications	UL, ISTA, RoHS, REACH
Standards	UL 2416

PACKAGE

Package contents	Baying hardware

WARRANTY

Warranty	60 months (5 years)

03 Engineered, delivered & supported by ServerInvest

Engineering & sizing
Selected and sized against your real IT load, room and redundancy targets.

Installation
Delivery, installation and commissioning by our engineers across Europe.

Certified processes
ISO 9001, ISO 14001 and ISO 27001 certified project delivery.

Service & support
Maintenance, spare parts and support from a single partner.

NATCERT ISO 9001 · NATCERT ISO 14001 · NATCERT ISO 27001 · cisco · tp-link · Omada by tp-link

Interested in this solution?

Request a quotation online or talk to a solutions engineer — we reply within one business day.
office@serverinvest.com