TECHNICAL DATASHEET

APC · SERVER RACKS

APC NetShelter SX Advanced 52U 750 mm × 1295 mm high-strength server rack, with shock packaging, black

52U high-strength AI/HPC enclosure, 750 × 1295 × 2436 mm, 1927.8 kg static, shock-packaged

SKU AR9558SPB2 | 52U | APC



HEIGHT IN U	EXTERNAL DIMENSIONS	MANUFACTURER	PRICE
52U	2436 × 750 × 1295 mm	APC by Schneider Electric	On request

ISO 9001 · ISO 14001 · ISO 27001 · cisco · tp-link · Omada by tp-link

REQUEST A QUOTATION ONLINE

serverinvest.com/product/apc-ar9558spb2

01 Product overview

The APC AR9558SPB2 is a NetShelter SX Advanced enclosure - Schneider Electric's taller, deeper and stronger rack platform aimed at AI, HPC and other high-density deployments. It offers 52U of 19-inch space in a 750 mm wide, 1295 mm deep frame standing 2436 mm tall, leaving room for very deep servers, power distribution, liquid-cooling manifolds and heavy cabling.

Vertical and horizontal steel bracing give a rating of 1927.8 kg static and 1587.6 kg dynamic load. The 12-gauge EIA rails adjust in 12.7 mm steps for equipment from 292 mm to 1143 mm deep, and four full-height 0U accessory channels at the rear take rack PDUs and cable managers.

This SP model ships in ISTA-tested shock packaging so the rack can be integrated off-site, loaded with IT equipment and then transported to its final location (shipping load up to 1600 kg according to APC), with a reusable ramp for pallet removal. 80% perforated front (curved) and rear doors swing 130°, split lockable side panels and 3-point key locking secure the rack, and the roof provides four extra-large cable entry points.

Casters, levelling feet and baying hardware are included; the enclosure is UL listed, RoHS/REACH compliant and carries a 5-year warranty.

KEY SPECIFICATIONS

Manufacturer	**APC by Schneider Electric**
Model	**AR9558SPB2**
Series	**NetShelter SX Advanced**
Height in U	**52U**
External dimensions (H × W × D)	**2436 × 750 × 1295 mm**
Usable equipment depth	**292–1143 mm**
Unit weight	**305 kg**
Mounting rails	**19" EIA-310 mounting rails**
Rail depth adjustment	**12.7 mm (0.5 in) increments**
0U accessory mounting	**4 full-height rear 0U accessory channels**
Static load rating	**1927.8 kg**
Dynamic load rating	**1587.6 kg**

HIGHLIGHTS

- 52U, 750 × 1295 mm footprint, 2436 mm tall - room for deep AI/HPC servers
- 1927.8 kg static / 1587.6 kg dynamic load
- Equipment depth 292–1143 mm, four 0U accessory channels
- ISTA shock packaging for rack-and-ship deployment
- 80% perforated doors, split lockable side panels, 3-point locking
- 5-year warranty

02 Full specifications

GENERAL	
Manufacturer	APC by Schneider Electric
Model	AR9558SPB2
Series	NetShelter SX Advanced

DIMENSIONS	
Height in U	52U
External dimensions (H × W × D)	2436 × 750 × 1295 mm
Usable equipment depth	292–1143 mm
Unit weight	305 kg

MOUNTING	
Mounting rails	19" EIA-310 mounting rails

Rail depth adjustment	12.7 mm (0.5 in) increments
0U accessory mounting	4 full-height rear 0U accessory channels

LOAD

Static load rating	1927.8 kg
Dynamic load rating	1587.6 kg
Shipping load (shock packaging)	1600 kg

DOORS & PANELS

Front door	Curved, perforated, reversible, 130° swing
Rear door	Perforated, flat, 130° swing
Door perforation	80%
Side panels	Split, lockable
Lock	3-point locking, key-locking handles

CONSTRUCTION

Cable entry	Roof with 4 extra-large cable entry points; bottom plate optional
Baying	Baying kit included
Casters / feet	Casters and levelling feet included
Colour	Black
Material	Steel; 12 gauge EIA mounting rail, 16 gauge front door, 16 gauge post, 18 gauge rear door, 18 gauge roof, 18 gauge side panels

PACKAGE

Packaging	ISTA shock packaging with reusable ramp
Package contents	Baying hardware, Key(s), Leveling feet, Mounting hardware, Pre-installed casters, Side panels

COMPLIANCE

Certifications	UL, ISTA, RoHS, REACH
Standards	EIA-310E

WARRANTY

Warranty	60 months (5 years)

03 Engineered, delivered & supported by ServerInvest

Engineering & sizing
Selected and sized against your real IT load, room and redundancy targets.

Installation
Delivery, installation and commissioning by our engineers across Europe.

Certified processes
ISO 9001, ISO 14001 and ISO 27001 certified project delivery.

Service & support
Maintenance, spare parts and support from a single partner.

NATCERT ISO 9001 · NATCERT ISO 14001 · NATCERT ISO 27001 · CISCO · tp-link · Omada by tp-link

Interested in this solution?

Request a quotation online or talk to a solutions engineer — we reply within one business day.
office@serverinvest.com