TECHNICAL DATASHEET

APC · SERVER RACKS

APC Easy Rack 42U 800 mm × 1000 mm rack cabinet, with side panels, no bottom, black

42U Easy Rack, 800 × 1000 × 1991 mm, 1199.8 kg static load

SKU ER8202 | 42U | APC

HEIGHT IN U	EXTERNAL DIMENSIONS	MANUFACTURER	PRICE
42U	1991 × 800 × 1000 mm	APC by Schneider Electric	On request

REQUEST A QUOTATION ONLINE
serverinvest.com/product/apc-er8202

01 Product overview

The APC ER8202 is part of the Easy Rack range, Schneider Electric's straightforward, value-oriented IT enclosures for server rooms, IT closets and edge sites. It offers 42U of EIA-310 19-inch mounting space in a 800 mm wide, 1000 mm deep cabinet with an external height of 1991 mm; the 800 mm width also allows up to 16 1U vertical knockout panels between the front and rear rails for patch panels or small devices.

Load ratings are 1199.8 kg static and 599.6 kg dynamic, and the adjustable mounting rails accept equipment from 241.6 mm up to 838.2 mm deep. Four rear accessory brackets come pre-installed for toolless mounting of full-height vertical rack PDUs; additional brackets or accessory channels can be added later.

Ventilation is handled by a removable, reversible single front door and split rear doors with up to 81% hexagonal perforation. The multi-functional roof has brush-strip openings for cabling and is compatible with APC overhead cable troughs. Roof, side panels and doors are bonded to the frame, with extra external grounding points front and rear. Half-height side panels with lockable upper sections are included; the cabinet is supplied without a bottom plate.

Casters, levelling feet and keys are included and the rack ships pre-assembled. Easy Rack is listed to UL 2416, follows EIA-310-E and carries a 5-year warranty.

KEY SPECIFICATIONS

Manufacturer	**APC by Schneider Electric**
Model	**ER8202**
Series	**Easy Rack**
EAN	**0731304427889**
Height in U	**42U**
External dimensions (H × W × D)	**1991 × 800 × 1000 mm**
Usable equipment depth	**241.6–838.2 mm**
Unit weight	**128.4 kg**
Mounting rails	**19" EIA-310 mounting rails**
0U accessory mounting	**4 pre-installed rear accessory brackets (toolless PDU mounting)**
Vertical patching	**Up to 16 × 1U vertical knockout panels**
Static load rating	**1199.8 kg**

HIGHLIGHTS

- 42U EIA-310 19" space, 800 × 1000 mm footprint, 1991 mm tall
- 1199.8 kg static / 599.6 kg dynamic load
- Equipment depth 241.6–838.2 mm, 4 pre-installed rear PDU brackets
- Vented front door and split rear doors, up to 81% perforation
- Lockable half-height side panels, integrated grounding
- Casters and levelling feet, 5-year warranty

02 Full specifications

GENERAL	
Manufacturer	APC by Schneider Electric
Model	ER8202
Series	Easy Rack
EAN	0731304427889

DIMENSIONS

Height in U	42U
External dimensions (H × W × D)	1991 × 800 × 1000 mm
Usable equipment depth	241.6–838.2 mm
Unit weight	128.4 kg

MOUNTING

Mounting rails	19" EIA-310 mounting rails
0U accessory mounting	4 pre-installed rear accessory brackets (toolless PDU mounting)
Vertical patching	Up to 16 × 1U vertical knockout panels

LOAD

Static load rating	1199.8 kg
Dynamic load rating	599.6 kg

DOORS & PANELS

Front door	Single vented door, removable and reversible
Rear door	Split vented doors
Door perforation	Up to 81%, hexagonal pattern
Side panels	Half-height, lockable top panels

CONSTRUCTION

Bottom plate	Not included
Cable entry	Roof openings with brush strips
Grounding	Roof, side panels and doors grounded to frame; external grounding points front and rear
Casters / feet	Pre-installed casters and levelling feet
Assembly	Pre-assembled
Colour	Black
Material	Steel; 18 gauge front door, 19 gauge rear door, 16 gauge post, 11 gauge EIA mounting rail

COMPLIANCE

Standards	UL 2416, UL 60950-1, EIA-310E

PACKAGE

Package contents	Baying hardware, Key(s), Keyed-alike doors and side panels, Leveling feet, Mounting hardware, Pre-installed casters

WARRANTY

Warranty	60 months (5 years)

03 Engineered, delivered & supported by ServerInvest

Engineering & sizing
Selected and sized against your real IT load, room and redundancy targets.

Installation
Delivery, installation and commissioning by our engineers across Europe.

Certified processes
ISO 9001, ISO 14001 and ISO 27001 certified project delivery.

Service & support
Maintenance, spare parts and support from a single partner.

NATCERT ISO 9001 · NATCERT ISO 14001 · NATCERT ISO 27001 · CISCO · tp-link · Omada by tp-link

Interested in this solution?

Request a quotation online or talk to a solutions engineer — we reply within one business day.
office@serverinvest.com