

TECHNICAL DATASHEET

SUPERMICRO · RACKMOUNT SERVERS

Supermicro 1U MegaDC Server ASG-1014S-ACR12N4H

1U UP internal-mounted storage server with 12 hot-swap 3.5" SAS/SATA + 4 7mm 2.5" U.2 NVMe and PCIe 4.0

SKU ASG-1014S-ACR12N4H

1U

Supermicro



FORM FACTOR

1U

MAX POWER (BASE)

306 W

HEAT OUTPUT

1,044 BTU/h

PRICE

On request

REQUEST A QUOTATION ONLINE

serverinvest.com/product/asg-1014s-acr12n4h

01 Product overview

The Supermicro ASG-1014S-ACR12N4H is a 1U MegaDC Server built on Single Socket SP3 AMD EPYC 7003/7002 Series Processor with up to 8 TB of memory in 16 DIMM slots.

1U UP internal-mounted storage server with 12 hot-swap 3.5" SAS/ SATA + 4 7mm 2.5" U.2 NVMe and PCIe 4.0.


ServerInvest configures every ASG-1014S-ACR12N4H to order, updates BIOS and BMC firmware, installs your operating system on request and runs a 48-hour burn-in test before delivery. Every system includes a 3-year warranty.

HIGHLIGHTS

- Single Socket SP3 AMD EPYC 7003/7002 Series Processor
- Up to 8 TB memory · 16 DIMM slots
- Total 16 bays 12 internal hot-swap 3.5" SAS/SATA drive bays
- Power: 2x 800W
- Networking: 2 RJ45 10GBASE-T with Broadcom BCM57416

KEY SPECIFICATIONS


Form factor	1U
Processor	Single Socket SP3 AMD EPYC 7003/7002 Series Processor
Memory	16 DIMM slots, up to 8 TB
Drive bays	16 (16 NVMe)
Power supply	2× 800 W
Typical power draw	450 W
Networking	2 RJ45 10GBASE-T with Broadcom BCM57416
Dimensions (W×H×D)	437 × 44 mm



02 Power & thermal

Calculated for the base configuration

IDLE	TYPICAL	MAXIMUM	HEAT (MAX)	COOLING	PSU LOAD
73 W	190 W	306 W	1,044 BTU/h	0.3 kW	38%




Annual IT energy (24/7)	1,357 kWh
Annual facility energy (PUE 1.5)	2,036 kWh
Annual energy cost	€271 IT · €407 incl. cooling (at 0.20 €/kWh)
CO ₂ emissions / year	0.53 t (grid factor 0.26 kg/kWh)
Power supplies	2× 800 W redundant (N+1)

POWER BY COMPONENT	IDLE	TYPICAL	MAX
Chassis, motherboard, fans, BMC	38 W	59 W	85 W
CPU (base configuration)	25 W	110 W	185 W
2× Memory (base configuration)	6 W	10 W	18 W

DC loads converted to wall power at 94% PSU efficiency; typical load assumed 70% of the time. Engineering estimates — confirm with the manufacturer's power calculator for critical designs.

03 Power connection diagram

Dual-feed (A/B) connection for redundant power supplies



- Connect PSU 1 to PDU-A and PSU 2 to PDU-B (independent feeds) using IEC C13/C14 (10 A) power cords.
- Maximum current per feed: 1.4 A at 230 V — each feed must be able to carry the full load if the other fails.
- Recommended protection per PDU circuit: MCB 6 A, curve C; RCD according to local regulations.
- Heat to remove at full load: 306 W = 1,044 BTU/h (0.3 kW).

04 Full specifications

MOTHERBOARD

Super H12SSW-NTR

PROCESSOR

CPU	Single Socket SP3 AMD EPYC 7003/7002 Series Processor
Note	Supports up to 240W TDP CPUs (Air Cooled)

SYSTEM MEMORY

Memory	Slot Count: 16 DIMM slots/8 Channels Max Memory (2DPC): Up to 8TB 3200MT/s ECC DDR4 RDIMM/LRDIMM View Memory Options
Memory Voltage	1.2V

ON-BOARD DEVICES

SAS	SAS (12Gbps) via Broadcom 3916; RAID 0/1/5/6/10/50/60 support
NVMe	NVMe; (Native) View NVMe Options
Network Connectivity	2 RJ45 10GBASE-T with Broadcom BCM57416 View AOC Options

INPUT / OUTPUT

LAN	1 RJ45 1 GbE Dedicated BMC LAN port 2 RJ45 10 GBASE-T LAN ports (Broadcom BCM57416)
USB	2 USB 2.0 Type-A ports (front) 4 USB 3.0 Type-A ports (Rear)
Video	1 VGA port (Rear)

Serial	1 COM port (Rear)
DOM	2 Super DOM (Disk on Module) ports with built-in power
TPM	1 TPM header

SYSTEM BIOS

BIOS Type	AMI 256MB SPI Flash EEPROM
-----------	----------------------------

MANAGEMENT

Software	SuperCloud Composer (SCC) Supermicro Server Manager (SSM) Supermicro Update Manager (SUM) Supermicro SuperDoctor 5 (SD5) Super Diagnostics Offline (SDO) Supermicro Thin-Agent Service (TAS) SuperServer Automation Assistant (SAA) New!
----------	--

Power configurations	ACPI/APM Power Management
----------------------	---------------------------

SECURITY

Hardware	Trusted Platform Module (TPM) 2.0 Silicon Root of Trust (RoT) – NIST 800-193 Compliant
----------	---

Features	Cryptographically Signed Firmware Secure Boot Secure Firmware Updates Automatic Firmware Recovery System Lockdown
----------	---

PC HEALTH MONITORING

CPU	4+1 Phase-switching voltage regulator Monitors for CPU Cores, Chipset Voltages, Memory
-----	---

Fan	Fans with tachometer monitoring Pulse Width Modulated (PWM) fan connectors Status monitor for speed control
-----	---

Temperature	Monitoring for CPU and chassis environment Thermal Control for fan connectors
-------------	--

CHASSIS

Form Factor	1U Rackmount
-------------	--------------

Model	CSE-802TS-R804WBP
-------	-------------------

DIMENSIONS AND WEIGHT

Height	1.7"
--------	------

Width	17.6"
-------	-------

Depth	37"
-------	-----

Package	12" (H) x 27" (W) x 53.15" (D)
---------	--------------------------------

Weight	Gross Weight: 58 lbs (26.3 kg) Net Weight: 39.5 lbs (17.9 kg)
--------	--

Available Color	Black
-----------------	-------

FRONT PANEL

Buttons	Power On/Off Power On/Off
LED	HDD activity Network activity Power status System information (overheat/UID) System information (overheat/UID)

EXPANSION SLOTS

PCI-Express (PCIe) Configuration	Default 1 PCIe 4.0 x16 (in x16) HHHL slot 2 PCIe 4.0 x16 (in x16) FHHL slots View AOC Options
M.2	2 M.2 PCIe 4.0 x2 NVMe slots (M-key 22110(default)/2280)

DRIVE BAYS / STORAGE

Drive Bays Configuration	Default: Total 16 bays 12 internal hot-swap 3.5" SAS/SATA drive bays 4 front hot-swap 7mm PCIe 4.0 x2 NVMe drive bays View NVMe Options View Drive Options
M.2	2 M.2 PCIe 4.0 x2 NVMe slots (M-key 22110(default)/2280) View M.2 Options

SYSTEM COOLING

Fans	Up to 6 Heavy Duty 4cm Fan(s)
Air Shroud	1 Air Shroud

POWER SUPPLY

2x 800W
2x 800W Redundant (1 + 1) Platinum Level (94%) power supplies
Dimension (WxHxL)
54.5 x 40.25 x 220 mm

OPERATING ENVIRONMENT

RoHS	RoHS Compliant
Environmental Spec.	Operating Temperature: 10°C to 35°C (50°F to 95°F) Non-operating Temperature: -40°C to 60°C (-40°F to 140°F) Operating Relative Humidity: 8% to 90% (Non-Condensing) Non-operating Relative Humidity: 5% to 95% (Non-Condensing)

05 Built, tested & supported by ServerInvest

Engineered configuration

Every option validated for socket, memory channels, PCIe lanes, power and cooling.

48-hour burn-in

Assembled, firmware-updated and stress-tested before it leaves our workshop.

3-year warranty

Standard on every system, with on-site next-business-day upgrades available.

Rack-ready delivery

Rails, cable management and labelling included — delivered across Europe.



Interested in this solution?

Request a quotation online or talk to a solutions engineer — we reply within one business day.
office@serverinvest.com

Official manufacturer datasheet: serverinvest.com/product/asg-1014s-acr12n4h/datasheet/manufacture

