

TECHNICAL DATASHEET

CISCO · NETWORKING

Cisco Catalyst 1200 8-port Gigabit switch

Catalyst 1200 smart managed switch - 8x 10/100/1000 RJ-45 ports

SKU C1200-8T-D

Desktop

Cisco



DOWNLINK PORTS

8x 10/100/1000 RJ-45 ports

SWITCHING CAPACITY

16 Gbps

DIMENSIONS

160 x 128 x 30 mm (W x D x H)

PRICE

On request

REQUEST A QUOTATION ONLINE

serverinvest.com/product/cisco-c1200-8t-d

01 Product overview

The Cisco C1200-8T-D is a Catalyst 1200 smart managed switch that provides 8x 10/100/1000 RJ-45 ports. It delivers 16 Gbps of switching capacity and a forwarding rate of 11.9 Mpps, ensuring wire-speed performance for everyday business traffic. Its fanless design keeps operation completely silent, so it can be installed close to users.

Catalyst 1200 switches are smart managed models designed for small and growing businesses that want enterprise-grade reliability without complexity. They offer an intuitive web interface and CLI, IPv4/IPv6 static routing, VLANs, QoS, access control lists, IEEE 802.1X authentication and Energy Efficient Ethernet, and can be managed at scale with Cisco Business Dashboard and the Cisco Business mobile app.

It is a dependable choice for offices, retail outlets, schools and growing SMB networks. ServerInvest supplies Cisco switching across Europe - contact us for pricing, availability and project quotes.

HIGHLIGHTS

- 8x 10/100/1000 RJ-45 ports
- 16 Gbps switching capacity, 11.9 Mpps forwarding rate
- Web GUI, CLI and Cisco Business Dashboard / mobile app management
- Layer 3 static routing, VLANs, QoS and 802.1X security
- Limited lifetime warranty



02 Full specifications

GENERAL

Manufacturer part number	C1200-8T-D
Series	Catalyst 1200
Switch type	Layer 2+ (static routing, up to 32 static routes)

PORTS

Downlink ports	8x 10/100/1000 RJ-45 ports
----------------	----------------------------

PERFORMANCE

Switching capacity	16 Gbps
Forwarding rate	11.9 Mpps

KEY SPECIFICATIONS

Manufacturer part number	C1200-8T-D
Series	Catalyst 1200
Switch type	Layer 2+ (static routing, up to 32 static routes)
Downlink ports	8x 10/100/1000 RJ-45 ports
Switching capacity	16 Gbps
Forwarding rate	11.9 Mpps
MAC address table	8,000
VLANs	255 active VLANs
Jumbo frames	9,000 bytes
CPU	Dual-core ARM 1.4 GHz
DRAM	1 GB DDR4
Flash	512 MB

MAC address table	8,000
VLANs	255 active VLANs
Jumbo frames	9,000 bytes

HARDWARE

CPU	Dual-core ARM 1.4 GHz
DRAM	1 GB DDR4
Flash	512 MB
Stacking	Not supported

POWER

Power supply	External power adapter
Power consumption (typical/system)	7.03 W
Heat dissipation	24.2 BTU/hr

PHYSICAL

Form factor	Desktop / wall-mountable
Dimensions	160 x 128 x 30 mm (W x D x H)
Weight	0.54 kg (1.19 lb)
Cooling	Fanless

ENVIRONMENTAL

Operating temperature	-5°C to +50°C
MTBF	3,277,956 hours

WARRANTY

Warranty	Limited lifetime warranty
----------	---------------------------

03 Engineered, delivered & supported by ServerInvest

Engineering & sizing

Selected and sized against your real IT load, room and redundancy targets.

Installation

Delivery, installation and commissioning by our engineers across Europe.

Certified processes

ISO 9001, ISO 14001 and ISO 27001 certified project delivery.

Service & support

Maintenance, spare parts and support from a single partner.



Interested in this solution?

Request a quotation online or talk to a solutions engineer — we reply within one business day.
office@serverinvest.com

