TECHNICAL DATASHEET

CISCO · NETWORKING

# Cisco Catalyst 9200L 48-port Gigabit partial PoE+ switch, 4x 1G SFP uplinks, Network Essentials

Catalyst 9200L fixed-uplink campus access switch - 48x 10/100/1000 ports with partial PoE+, 4x 1G SFP uplinks, 370W PoE budget

SKU C9200L-48PL-4G-E | 1U | Cisco



| DOWNLINK PORTS | SWITCHING CAPACITY | DIMENSIONS | PRICE |
|---|---|---|---|
| 48x 10/100/1000 ports with partial PoE+ | 104 Gbps | 4.4 x 44.5 x 28.8 cm (1.73 x 17.5 x 11... | On request |

ISO 9001 · ISO 14001 · ISO 27001

REQUEST A QUOTATION ONLINE

serverinvest.com/product/cisco-c9200l-48pl-4g-e

## 01 Product overview

The Cisco C9200L-48PL-4G-E is a Catalyst 9200L fixed-uplink campus access switch that provides 48x 10/100/1000 ports with partial PoE+ and 4x 1G SFP fixed uplinks, with a 370 W PoE+ (802.3at) power budget for phones, wireless access points and cameras. It delivers 104 Gbps of switching capacity and a forwarding rate of 77.38 Mpps, ensuring wire-speed performance for everyday business traffic.

The Catalyst 9200L variants keep the Cisco IOS XE software foundation of the Catalyst 9000 family while using fixed uplinks and a shallower chassis, making them a cost-optimised choice for wiring closets and branch offices. They support Layer 3 routing, StackWise-80 stacking, field-replaceable power supplies, Cisco DNA Center/Catalyst Center automation and the Cisco Trustworthy Solutions security stack, including secure boot and signed images.

This part number ships with the Network Essentials software license; Network Essentials covers the Layer 2 and Layer 3 access feature set, with an upgrade path to Network Advantage. A Cisco DNA / Catalyst subscription is ordered together with the switch. It is well suited to enterprise wiring closets, branch offices and campus access layers where powered endpoints such as IP phones, Wi-Fi access points and security cameras need to be supported. ServerInvest supplies Cisco switching across Europe - contact us for pricing, availability and project quotes.

### KEY SPECIFICATIONS

| | |
|---|---|
| Manufacturer part number | **C9200L-48PL-4G-E** |
| Series | **Catalyst 9200L** |
| Switch type | **Layer 3 (Cisco IOS XE)** |
| Downlink ports | **48x 10/100/1000 ports with partial PoE+** |
| Uplinks | **4x 1G SFP fixed uplinks** |
| PoE standard | **PoE+ (802.3at), partial** |
| PoE budget | **370 W (single default power supply)** |
| Switching capacity | **104 Gbps** |
| Forwarding rate | **77.38 Mpps** |
| MAC address table | **16,000** |
| VLANs | **4,094** |
| Jumbo frames | **9,198 bytes** |

### HIGHLIGHTS

- 48x 10/100/1000 ports with partial PoE+ with 370 W PoE+ (802.3at) budget
- 4x 1G SFP fixed uplinks
- 104 Gbps switching capacity, 77.38 Mpps forwarding rate
- Cisco IOS XE with Catalyst Center (DNA Center) automation and assurance
- StackWise-80 stacking of up to 8 switches
- Enhanced Limited Lifetime Warranty (E-LLW)

## 02 Full specifications

| GENERAL | |
|---|---|
| Manufacturer part number | C9200L-48PL-4G-E |
| Series | Catalyst 9200L |
| Switch type | Layer 3 (Cisco IOS XE) |
| License tier | Network Essentials (Cisco DNA / Catalyst subscription ordered separately) |

| PORTS | |
|---|---|
| Downlink ports | 48x 10/100/1000 ports with partial PoE+ |
| Uplinks | 4x 1G SFP fixed uplinks |

## POWER OVER ETHERNET

| | |
|---|---|
| PoE standard | PoE+ (802.3at), partial |
| PoE budget | 370 W (single default power supply) |

## PERFORMANCE

| | |
|---|---|
| Switching capacity | 104 Gbps |
| Forwarding rate | 77.38 Mpps |
| MAC address table | 16,000 |
| VLANs | 4,094 |
| Jumbo frames | 9,198 bytes |
| Routing scale | 11,000 IPv4 (ARP + learned); 3,000 IPv4 routing entries |

## HARDWARE

| | |
|---|---|
| DRAM | 2 GB |
| Flash | 4 GB |
| Stacking | StackWise-80 (80 Gbps), up to 8 switches |

## POWER

| | |
|---|---|
| Power supply | PWR-C5-600WAC (600W AC), field-replaceable, dual redundant slots (740W PoE with two PSUs) |
| Power consumption (typical/system) | 47.57 W |
| Power consumption (maximum, incl. PoE load) | 466.34 W |

## PHYSICAL

| | |
|---|---|
| Form factor | 1U rack-mountable |
| Dimensions | 4.4 x 44.5 x 28.8 cm (1.73 x 17.5 x 11.3 in) |
| Weight | 4.80 kg (10.58 lb) |
| Cooling | Fixed redundant fans |

## ENVIRONMENTAL

| | |
|---|---|
| Operating temperature | -5°C to +45°C |
| MTBF | 347,760 hours |

## WARRANTY

| | |
|---|---|
| Warranty | Enhanced Limited Lifetime Warranty (E-LLW) |

## 03 Engineered, delivered & supported by ServerInvest

### Engineering & sizing
Selected and sized against your real IT load, room and redundancy targets.

### Installation
Delivery, installation and commissioning by our engineers across Europe.

### Certified processes
ISO 9001, ISO 14001 and ISO 27001 certified project delivery.

### Service & support
Maintenance, spare parts and support from a single partner.

NATCERT ISO 9001 · NATCERT ISO 14001 · NATCERT ISO 27001 · CISCO · tp-link · Omada by tp-link

## Interested in this solution?

Request a quotation online or talk to a solutions engineer — we reply within one business day.
office@serverinvest.com