TECHNICAL DATASHEET

CISCO · NETWORKING

# Cisco Catalyst 9300L 24-port Gigabit PoE+ switch, 4x 1G SFP uplinks, Network Essentials

Catalyst 9300L fixed-uplink enterprise access switch - 24x 10/100/1000 PoE+ ports, 4x 1G SFP uplinks, 505W PoE budget

SKU C9300L-24P-4G-E | 1U | Cisco

| DOWNLINK PORTS | SWITCHING CAPACITY | DIMENSIONS | PRICE |
|---|---|---|---|
| 24x 10/100/1000 PoE+ ports | 56 Gbps | 4.4 x 44.5 x 40.9 cm (1.73 x 17.5 x 16... | On request |

ISO 9001 · ISO 14001 · ISO 27001

REQUEST A QUOTATION ONLINE

serverinvest.com/product/cisco-c9300l-24p-4g-e

## 01 Product overview

The Cisco C9300L-24P-4G-E is a Catalyst 9300L fixed-uplink enterprise access switch that provides 24x 10/100/1000 PoE+ ports and 4x 1G SFP fixed uplinks, with a 505 W PoE+ (802.3at) power budget for phones, wireless access points and cameras. It delivers 56 Gbps of switching capacity and a forwarding rate of 41.66 Mpps, ensuring wire-speed performance for everyday business traffic.

The Catalyst 9300L delivers the Catalyst 9300 feature set - Cisco IOS XE, UADP 2.0 forwarding, SD-Access, MACsec and Catalyst Center automation - with fixed uplinks for deployments that do not need modular network modules. StackWise-320 stacking, field-replaceable platinum-rated power supplies and fans, and full Layer 3 routing make it a strong fit for enterprise wiring closets that want Catalyst 9300-class software at a lower entry point.

This part number ships with the Network Essentials software license; Network Essentials covers the Layer 2 and Layer 3 access feature set, with an upgrade path to Network Advantage. A Cisco DNA / Catalyst subscription is ordered together with the switch. It is well suited to enterprise wiring closets, branch offices and campus access layers where powered endpoints such as IP phones, Wi-Fi access points and security cameras need to be supported. ServerInvest supplies Cisco switching across Europe - contact us for pricing, availability and project quotes.

### KEY SPECIFICATIONS

| | |
|---|---|
| Manufacturer part number | **C9300L-24P-4G-E** |
| Series | **Catalyst 9300L** |
| Switch type | **Layer 3 (Cisco IOS XE)** |
| Downlink ports | **24x 10/100/1000 PoE+ ports** |
| Uplinks | **4x 1G SFP fixed uplinks** |
| PoE standard | **PoE+ (802.3at)** |
| PoE budget | **505 W (single default power supply)** |
| Switching capacity | **56 Gbps** |
| Forwarding rate | **41.66 Mpps** |
| MAC address table | **32,000** |
| VLANs | **4,094** |
| Jumbo frames | **9,198 bytes** |

### HIGHLIGHTS

- 24x 10/100/1000 PoE+ ports with 505 W PoE+ (802.3at) budget
- 4x 1G SFP fixed uplinks
- 56 Gbps switching capacity, 41.66 Mpps forwarding rate
- Catalyst 9300 software and security feature set with fixed uplinks
- StackWise-320 stacking of up to 8 switches
- Enhanced Limited Lifetime Warranty (E-LLW)

## 02 Full specifications

| GENERAL | |
|---|---|
| Manufacturer part number | C9300L-24P-4G-E |
| Series | Catalyst 9300L |
| Switch type | Layer 3 (Cisco IOS XE) |
| License tier | Network Essentials (Cisco DNA / Catalyst subscription ordered separately) |

## PORTS

| | |
|---|---|
| Downlink ports | 24x 10/100/1000 PoE+ ports |
| Uplinks | 4x 1G SFP fixed uplinks |

## POWER OVER ETHERNET

| | |
|---|---|
| PoE standard | PoE+ (802.3at) |
| PoE budget | 505 W (single default power supply) |

## PERFORMANCE

| | |
|---|---|
| Switching capacity | 56 Gbps |
| Forwarding rate | 41.66 Mpps |
| MAC address table | 32,000 |
| VLANs | 4,094 |
| Jumbo frames | 9,198 bytes |
| Routing scale | 32,000 IPv4 (24,000 direct + 8,000 indirect); 16,000 IPv6 |

## HARDWARE

| | |
|---|---|
| DRAM | 8 GB |
| Flash | 16 GB |
| Stacking | StackWise-320 (320 Gbps), up to 8 switches |

## POWER

| | |
|---|---|
| Power supply | PWR-C1-715WAC-P (715W AC) platinum, field-replaceable, dual redundant slots, StackPower |

## PHYSICAL

| | |
|---|---|
| Form factor | 1U rack-mountable |
| Dimensions | 4.4 x 44.5 x 40.9 cm (1.73 x 17.5 x 16.1 in) chassis |
| Weight | 6.81 kg (14.99 lb) |
| Cooling | Field-replaceable redundant fans |

## ENVIRONMENTAL

| | |
|---|---|
| Operating temperature | -5°C to +45°C |
| MTBF | 346,940 hours |

## WARRANTY

| | |
|---|---|
| Warranty | Enhanced Limited Lifetime Warranty (E-LLW) |

## 03 Engineered, delivered & supported by ServerInvest

### Engineering & sizing
Selected and sized against your real IT load, room and redundancy targets.

### Installation
Delivery, installation and commissioning by our engineers across Europe.

### Certified processes
ISO 9001, ISO 14001 and ISO 27001 certified project delivery.

### Service & support
Maintenance, spare parts and support from a single partner.

NATCERT ISO 9001 · NATCERT ISO 14001 · NATCERT ISO 27001 · cisco · tp-link · Omada by tp-link

## Interested in this solution?

Request a quotation online or talk to a solutions engineer — we reply within one business day.
office@serverinvest.com