

TECHNICAL DATASHEET

CISCO • NETWORKING

Cisco Catalyst 9300L 48-port Gigabit switch, 4x 1G SFP uplinks, Network Essentials

Catalyst 9300L fixed-uplink enterprise access switch - 48x 10/100/1000 RJ-45 data ports, 4x 1G SFP uplinks

SKU C9300L-48T-4G-E

1U

Cisco



DOWNLINK PORTS

48x 10/100/1000 RJ-45
data ports

SWITCHING CAPACITY

104 Gbps

DIMENSIONS

4.4 x 44.5 x 40.9 cm (1.73
x 17.5 x 16...

PRICE

On request



REQUEST A QUOTATION ONLINE

serverinvest.com/product/cisco-c9300l-48t-4g-e



01 Product overview

The Cisco C9300L-48T-4G-E is a Catalyst 9300L fixed-uplink enterprise access switch that provides 48x 10/100/1000 RJ-45 data ports and 4x 1G SFP fixed uplinks. It delivers 104 Gbps of switching capacity and a forwarding rate of 77.38 Mpps, ensuring wire-speed performance for everyday business traffic.

The Catalyst 9300L delivers the Catalyst 9300 feature set - Cisco IOS XE, UADP 2.0 forwarding, SD-Access, MACsec and Catalyst Center automation - with fixed uplinks for deployments that do not need modular network modules. StackWise-320 stacking, field-replaceable platinum-rated power supplies and fans, and full Layer 3 routing make it a strong fit for enterprise wiring closets that want Catalyst 9300-class software at a lower entry point.

This part number ships with the Network Essentials software license; Network Essentials covers the Layer 2 and Layer 3 access feature set, with an upgrade path to Network Advantage. A Cisco DNA / Catalyst subscription is ordered together with the switch. It is well suited to enterprise wiring closets, branch offices and campus access layers. ServerInvest supplies Cisco switching across Europe - contact us for pricing, availability and project quotes.

KEY SPECIFICATIONS

Manufacturer part number	C9300L-48T-4G-E
Series	Catalyst 9300L
Switch type	Layer 3 (Cisco IOS XE)
Downlink ports	48x 10/100/1000 RJ-45 data ports
Uplinks	4x 1G SFP fixed uplinks
Switching capacity	104 Gbps
Forwarding rate	77.38 Mpps
MAC address table	32,000
VLANs	4,094
Jumbo frames	9,198 bytes
Routing scale	32,000 IPv4 (24,000 direct + 8,000 indirect); 16,000 IPv6
DRAM	8 GB

HIGHLIGHTS

- 48x 10/100/1000 RJ-45 data ports
- 4x 1G SFP fixed uplinks
- 104 Gbps switching capacity, 77.38 Mpps forwarding rate
- Catalyst 9300 software and security feature set with fixed uplinks
- StackWise-320 stacking of up to 8 switches
- Enhanced Limited Lifetime Warranty (E-LLW)

02 Full specifications

GENERAL

Manufacturer part number	C9300L-48T-4G-E
Series	Catalyst 9300L
Switch type	Layer 3 (Cisco IOS XE)
License tier	Network Essentials (Cisco DNA / Catalyst subscription ordered separately)

PORTS

Downlink ports	48x 10/100/1000 RJ-45 data ports
Uplinks	4x 1G SFP fixed uplinks

PERFORMANCE

Switching capacity	104 Gbps
Forwarding rate	77.38 Mpps
MAC address table	32,000
VLANs	4,094

Jumbo frames	9,198 bytes
Routing scale	32,000 IPv4 (24,000 direct + 8,000 indirect); 16,000 IPv6

HARDWARE

DRAM	8 GB
Flash	16 GB
Stacking	StackWise-320 (320 Gbps), up to 8 switches

POWER

Power supply	PWR-C1-350WAC-P (350W AC) platinum, field-replaceable, dual redundant slots, StackPower
--------------	---

PHYSICAL

Form factor	1U rack-mountable
Dimensions	4.4 x 44.5 x 40.9 cm (1.73 x 17.5 x 16.1 in) chassis
Weight	7.0 kg (15.41 lb)
Cooling	Field-replaceable redundant fans

ENVIRONMENTAL

Operating temperature	-5°C to +45°C
MTBF	387,860 hours

WARRANTY

Warranty	Enhanced Limited Lifetime Warranty (E-LLW)
----------	--

03 Engineered, delivered & supported by ServerInvest

Engineering & sizing

Selected and sized against your real IT load, room and redundancy targets.

Installation

Delivery, installation and commissioning by our engineers across Europe.

Certified processes

ISO 9001, ISO 14001 and ISO 27001 certified project delivery.

Service & support

Maintenance, spare parts and support from a single partner.



Interested in this solution?

Request a quotation online or talk to a solutions engineer — we reply within one business day.
office@serverinvest.com

