

TECHNICAL DATASHEET

CISCO • NETWORKING

Cisco Business 220 24-port Gigabit smart switch, 4x 10G SFP+ uplinks (UK power cord)

Business 220 smart switch - 24x 10/100/1000 RJ-45 ports, 4x 10G SFP+ uplinks

SKU CBS220-24T-4X-UK

1U

Cisco



DOWNLINK PORTS

24x 10/100/1000 RJ-45 ports

SWITCHING CAPACITY

128 Gbps

DIMENSIONS

440 x 203 x 44 mm (W x D x H)

PRICE

On request

REQUEST A QUOTATION ONLINE

serverinvest.com/product/cisco-cbs220-24t-4x-uk

01 Product overview

The Cisco CBS220-24T-4X-UK is a Business 220 smart switch that provides 24x 10/100/1000 RJ-45 ports and 4x 10G SFP+ uplinks. It delivers 128 Gbps of switching capacity and a forwarding rate of 95.23 Mpps, ensuring wire-speed performance for everyday business traffic.

Cisco Business 220 smart switches give small businesses easy-to-use management with an intuitive web interface, VLANs, QoS, IGMP snooping, link aggregation and port security, plus PoE+ on selected models. They can be deployed and monitored with the Cisco Business mobile app and Cisco Business Dashboard, making day-to-day operations simple for teams without dedicated network staff.



The -UK suffix denotes the United Kingdom power cord variant; hardware and features are identical to other regional versions. It is a dependable choice for offices, retail outlets, schools and growing SMB networks. ServerInvest supplies Cisco switching across Europe - contact us for pricing, availability and project quotes.

HIGHLIGHTS

- 24x 10/100/1000 RJ-45 ports
- 4x 10G SFP+ uplinks
- 128 Gbps switching capacity, 95.23 Mpps forwarding rate
- Smart management via web GUI, Cisco Business app and Dashboard
- VLANs, QoS, IGMP snooping and link aggregation

KEY SPECIFICATIONS

Manufacturer part number	CBS220-24T-4X-UK
Series	Business 220
Switch type	Layer 2 smart managed
Regional variant	UK (BS 1363) power cord
Downlink ports	24x 10/100/1000 RJ-45 ports
Uplinks	4x 10G SFP+ uplinks
Switching capacity	128 Gbps
Forwarding rate	95.23 Mpps
MAC address table	8,192
VLANs	256
Jumbo frames	9,216 bytes
Packet buffer	12 Mb



02 Full specifications

GENERAL

Manufacturer part number	CBS220-24T-4X-UK
Series	Business 220
Switch type	Layer 2 smart managed
Regional variant	UK (BS 1363) power cord

PORTS

Downlink ports	24x 10/100/1000 RJ-45 ports
Uplinks	4x 10G SFP+ uplinks

PERFORMANCE

Switching capacity	128 Gbps
Forwarding rate	95.23 Mpps
MAC address table	8,192
VLANs	256
Jumbo frames	9,216 bytes
Packet buffer	12 Mb

HARDWARE

DRAM	256 MB
Flash	64 MB
Stacking	Not supported

POWER

Power supply	Internal power supply
Power consumption (typical/system)	23.2 W
Heat dissipation	80.5 BTU/hr

PHYSICAL

Form factor	1U rack-mountable
Dimensions	440 x 203 x 44 mm (W x D x H)
Weight	2.69 kg (5.93 lb)
Cooling	1 fan (34 dB)

ENVIRONMENTAL

Operating temperature	0°C to +50°C
MTBF	1,372,359 hours

03 Engineered, delivered & supported by ServerInvest

Engineering & sizing

Selected and sized against your real IT load, room and redundancy targets.

Installation

Delivery, installation and commissioning by our engineers across Europe.

Certified processes

ISO 9001, ISO 14001 and ISO 27001 certified project delivery.

Service & support

Maintenance, spare parts and support from a single partner.



Interested in this solution?

Request a quotation online or talk to a solutions engineer — we reply within one business day.
office@serverinvest.com

