

TECHNICAL DATASHEET

DIGITUS • SERVER RACKS

DIGITUS 10" wall-mount 12U 10" wall-mount cabinet, 312 × 300 mm (W × D), black

254 mm (10") 12U wall mounting cabinet 592x312x300 mm, color black (RAL 9005)

SKU DN-10-12U-B

12U

Digitus



HEIGHT

12U

LOAD CAPACITY

30 kg

EXTERNAL DIMENSIONS

592 × 312 × 300 mm

PRICE

On request

REQUEST A QUOTATION ONLINE

serverinvest.com/product/digitus-dn-10-12u-b

01 Product overview

This DIGITUS 254 mm (10") wall-mounting cabinet is a compact, fully assembled enclosure for small switches, 10-inch patch panels and home-network equipment. A pair of depth-adjustable galvanized 10-inch rails, a lockable safety-glass door and cable entries in roof (with brush strip) and floor are fitted as standard.

This 12U model (part number DN-10-12U-B) measures 592 × 312 × 300 mm (H × W × D) and is finished in black (RAL 9005) electrostatic powder coating. It is equipped with a lockable safety-glass front door. The 10-inch rails accept equipment up to 240 mm deep. Rated load capacity is 30 kg. It is delivered fully assembled.

It suits home networks, small offices, smart-home and multimedia installations where space is limited. The cabinet can be completely dismantled if necessary and the door hinges can be changed to suit the installation.

HIGHLIGHTS

- 12U 10" network enclosure, 312 × 300 mm footprint
- Lockable safety-glass front door
- Equipment installation depth 240 mm
- Load capacity 30 kg
- IP20 protection, Black (RAL 9005)
- Supplied fully assembled

KEY SPECIFICATIONS

Manufacturer	DIGITUS (ASSMANN Electronic)
Part number	DN-10-12U-B
EAN	4016032474258
Series	10" wall-mount
Cabinet type	Wall mounting cabinet
Height (rack units)	12U
Mounting standard	254 mm (10")
External dimensions (H × W × D)	592 × 312 × 300 mm
Width	312 mm
Depth	300 mm
Height	592 mm
Load capacity	30 kg



02 Full specifications

GENERAL

Manufacturer	DIGITUS (ASSMANN Electronic)
Part number	DN-10-12U-B
EAN	4016032474258
Series	10" wall-mount
Cabinet type	Wall mounting cabinet
Height (rack units)	12U
Mounting standard	254 mm (10")

DIMENSIONS

External dimensions (H × W × D)	592 × 312 × 300 mm
---------------------------------	--------------------

Width	312 mm
Depth	300 mm
Height	592 mm

LOAD

Load capacity	30 kg
---------------	-------

DOORS & SECURITY

Front door	Glass door, single opening
Side panels	Both sides
Front door	Lockable safety glass door
Door opening angle	200° door opening angle
Front door	1-point locking on the front door

CONSTRUCTION

Colour	Black (RAL 9005)
Material	1.1 - 1.5 thick sheet steel with a high load-bearing capacity, powder-coated

PROTECTION

IP rating	IP20
Protection class	Protection class IP20

DELIVERY

Delivery state	Assembled
----------------	-----------

MOUNTING

19" rails	254 mm (10") profile rails mounted at the front inside the enclosure, galvanized
19" rails	254 mm (10") profile rails are adjustable in depth
Installation depth for components max.	240 mm

CABLE MANAGEMENT

Cable entry	Cable entry with brush strip in the roof and with plastic cover in the floor
-------------	--

COOLING

Ventilation	Ventilation slots for active and passive ventilation
-------------	--

GROUNDING

Earthing	Including earthing bolt on the housing base
----------	---

PACKAGE CONTENTS

Included	Installation set (screws, cage nuts, washers); 2x key
----------	---

LOGISTICS

Shipping weight

11.50 kg

03 Engineered, delivered & supported by ServerInvest

Engineering & sizing

Selected and sized against your real IT load, room and redundancy targets.

Installation

Delivery, installation and commissioning by our engineers across Europe.

Certified processes

ISO 9001, ISO 14001 and ISO 27001 certified project delivery.

Service & support

Maintenance, spare parts and support from a single partner.



Interested in this solution?

Request a quotation online or talk to a solutions engineer — we reply within one business day.
office@serverinvest.com

