

TECHNICAL DATASHEET

DIGITUS • SERVER RACKS

DIGITUS SOHO Slim 19" wall-mount cabinet, 3U rotatable + 2U fixed, grey

Wall mounting cabinet, SOHO, slim, 145x525x475 mm 3U rotatable, 2U fix, color grey (RAL 7035)

SKU DN-19 04U-PB

5U

Digitus



HEIGHT

3U rotatable + 2U fixed

LOAD CAPACITY

30 kg

EXTERNAL DIMENSIONS

145 × 525 × 475 mm

PRICE

On request



REQUEST A QUOTATION ONLINE

serverinvest.com/product/digitus-dn-19-04u-pb

01 Product overview

The DIGITUS SOHO Slim wall-mounting cabinet is a shallow, office-friendly enclosure with two independent 19-inch mounting options: a 3U rail at the front that can be rotated vertically, horizontally or at an angle, and a fixed 2U horizontal rail at the rear for passive components.

This 5U model (part number DN-19 04U-PB) measures 145 × 525 × 475 mm (H × W × D) and is finished in light grey (RAL 7035) electrostatic powder coating. It is equipped with a lockable safety-glass front door. The 19-inch mounting rails accept equipment with an installation depth of 265 mm. Rated load capacity is 30 kg. It is delivered fully assembled.

A punched mounting grid in the lower part of the housing also takes equipment that is not 19-inch compatible, such as DSL routers or smart-home controllers, making the cabinet ideal for home distribution boards, small offices and home automation.

HIGHLIGHTS

- 3U rotatable front rail plus 2U fixed rear rail
- Lockable safety-glass front door
- Equipment installation depth 265 mm
- Load capacity 30 kg
- IP20 protection, Light grey (RAL 7035)
- Supplied fully assembled

KEY SPECIFICATIONS

Manufacturer	DIGITUS (ASSMANN Electronic)
Part number	DN-19 04U-PB
EAN	4016032200109
Series	SOHO Slim
Cabinet type	Wall mounting cabinet, home automation
Height (rack units)	3U rotatable + 2U fixed
Mounting standard	483 mm (19")
External dimensions (H × W × D)	145 × 525 × 475 mm
Width	525 mm
Depth	475 mm
Height	145 mm
Load capacity	30 kg



02 Full specifications

GENERAL

Manufacturer	DIGITUS (ASSMANN Electronic)
Part number	DN-19 04U-PB
EAN	4016032200109
Series	SOHO Slim
Cabinet type	Wall mounting cabinet, home automation
Height (rack units)	3U rotatable + 2U fixed
Mounting standard	483 mm (19")

DIMENSIONS

External dimensions (H × W × D)	145 × 525 × 475 mm
---------------------------------	--------------------

Width	525 mm
Depth	475 mm
Height	145 mm

LOAD

Load capacity	30 kg
---------------	-------

DOORS & SECURITY

Front door	Glass door, single opening
Side panels	Both sides
Feature	Lockable housing with transparent polycarbonate pane
Feature	Steel door stop mechanism keeps the door open
Locking	1-point four-point locking

CONSTRUCTION

Colour	Light grey (RAL 7035)
Material	2.0 mm thick sheet steel with a high load-bearing capacity, powder-coated

PROTECTION

IP rating	IP20
Protection class	Protection class IP20

DELIVERY

Delivery state	Assembled
----------------	-----------

FEATURES

Feature	Upper part of the housing can be opened up to 80°
2 separate 483 mm (19") installation options	3U vertical (rotatable), 2U horizontal (fixed)
Feature	Lower housing area with punched-out mounting holes for mounting equipment that is not 483 mm (19") compatible

MOUNTING

Rails	Max. installation depth (from front vertical rail to stop on rear horizontal rail): Approx. 265 mm
Max. installation depth (from front vertical rail to rear wall stop)	Approx. 355 mm

CABLE MANAGEMENT

Cable entry	Pre-punched cut-outs for cable routing
Cable entry	Area for cable ties

COOLING

Ventilation	Ventilation slots for active and passive ventilation
Fan mount dimensions	57.5 x 57.5 mm
Hole spacing for fan mounting	50 x 50 mm (3.5 mm diameter)

PACKAGE CONTENTS

Included 2 x key

LOGISTICS

Shipping weight 9.50 kg

03 Engineered, delivered & supported by ServerInvest

Engineering & sizing

Selected and sized against your real IT load, room and redundancy targets.

Installation

Delivery, installation and commissioning by our engineers across Europe.

Certified processes

ISO 9001, ISO 14001 and ISO 27001 certified project delivery.

Service & support

Maintenance, spare parts and support from a single partner.



Interested in this solution?

Request a quotation online or talk to a solutions engineer — we reply within one business day.
office@serverinvest.com

