TECHNICAL DATASHEET

DIGITUS · SERVER RACKS

# DIGITUS Unique 9U 19" wall-mount cabinet, 600 × 450 mm (W × D), grey

9U wall mounting cabinet, Unique 509x600x450 mm, color grey (RAL 7035)

SKU DN-19 09-U | 9U | Digitus

| HEIGHT | LOAD CAPACITY | EXTERNAL DIMENSIONS | PRICE |
|---|---|---|---|
| 9U | 100 kg | 509 × 600 × 450 mm | On request |

ISO 9001 · ISO 14001 · ISO 27001 · cisco · tp-link · Omada by tp-link

REQUEST A QUOTATION ONLINE

serverinvest.com/product/digitus-dn-19-09-u

## 01 Product overview

The DIGITUS Unique wall-mounting cabinets bring the cable-management concept of the Unique floor-standing range to compact wall installations. A sliding cable inlet with foam seal in the roof, pre-cut inlets in the rear wall and floor and a prepared fan cut-out make cable routing and cooling straightforward. Lockable, removable side panels and a removable front door give full access during installation.

This 9U model (part number DN-19 09-U) measures 509 × 600 × 450 mm (H × W × D) and is finished in light grey (RAL 7035) electrostatic powder coating. It is equipped with a lockable safety-glass front door. The 19-inch mounting rails accept equipment with an installation depth of 370 mm. Rated load capacity is 100 kg. It is delivered fully assembled.

Wall installation takes two steps: the frame plate is screwed to the wall and the cabinet body is then attached to it. With optional levelling feet or castors the cabinet can also be used free-standing. Typical uses are sub-distribution points, small offices, retail branches and CCTV or telephony installations.

### KEY SPECIFICATIONS

| | |
|---|---|
| Manufacturer | **DIGITUS (ASSMANN Electronic)** |
| Part number | **DN-19 09-U** |
| EAN | **4016032135210** |
| Series | **Unique (wall-mount)** |
| Cabinet type | **Wall mounting cabinet** |
| Height (rack units) | **9U** |
| Mounting standard | **483 mm (19")** |
| External dimensions (H × W × D) | **509 × 600 × 450 mm** |
| Width | **600 mm** |
| Depth | **450 mm** |
| Height | **509 mm** |
| Load capacity | **100 kg** |

### HIGHLIGHTS

- 9U 19" network enclosure, 600 × 450 mm footprint
- Lockable safety-glass front door
- Equipment installation depth 370 mm
- Load capacity 100 kg
- IP20 protection, Light grey (RAL 7035)
- Supplied fully assembled

## 02 Full specifications

| GENERAL | |
|---|---|
| Manufacturer | DIGITUS (ASSMANN Electronic) |
| Part number | DN-19 09-U |
| EAN | 4016032135210 |
| Series | Unique (wall-mount) |
| Cabinet type | Wall mounting cabinet |
| Height (rack units) | 9U |
| Mounting standard | 483 mm (19") |

## DIMENSIONS

| | |
|---|---|
| External dimensions (H × W × D) | 509 × 600 × 450 mm |
| Width | 600 mm |
| Depth | 450 mm |
| Height | 509 mm |

## LOAD

| | |
|---|---|
| Load capacity | 100 kg |

## DOORS & SECURITY

| | |
|---|---|
| Front door | Glass door, single opening |
| Side panels | Both sides |
| Front door | Lockable safety-glass door with steel frame |
| Door opening angle | 210° door opening angle |
| Front door | 1-point-locking-mechanism on the front door |
| Side panels | Side panels are lockable and removable |

## CONSTRUCTION

| | |
|---|---|
| Colour | Light grey (RAL 7035) |

## PROTECTION

| | |
|---|---|
| IP rating | IP20 |
| Protection class | Safety class rating IP20 |

## DELIVERY

| | |
|---|---|
| Delivery state | Assembled |

## MOUNTING

| | |
|---|---|
| 19" rails | 483 mm (19“) profile rails mounted on the front- and rear side inside of the rack, galvanized |
| 19" rails | 483 mm (19“) profile rails are adjustable in depth and with height unit marking |
| Max. installation depth | 370 mm |
| Equipment mounting depth min.-max. | 305-370 mm |

## CABLE MANAGEMENT

| | |
|---|---|
| Cable entry | Cable entry on the rear side and base with plastic cover and top with sliding cover |

## COOLING

| | |
|---|---|
| Roof | Roof is prepared for fan units (punched out entries) |
| Ventilation | Ventilation slots for active and passive ventilation and exhausting |

## GROUNDING

| | |
|---|---|
| Earthing | Several earthing points for rack components |

## FEATURES

| | |
|---|---|
| Feature | Incl. installation set (screws, cage nuts, washers) |
| Delivery | Rack is completely mounted |

## PACKAGE CONTENTS

| | |
|---|---|
| Included | Earthing wire set; Installation set (screws, cage nuts, washers); 2 x Keys |

## LOGISTICS

| | |
|---|---|
| Shipping weight | 20.60 kg |

## 03 Engineered, delivered & supported by ServerInvest

### Engineering & sizing
Selected and sized against your real IT load, room and redundancy targets.

### Installation
Delivery, installation and commissioning by our engineers across Europe.

### Certified processes
ISO 9001, ISO 14001 and ISO 27001 certified project delivery.

### Service & support
Maintenance, spare parts and support from a single partner.

## Interested in this solution?

Request a quotation online or talk to a solutions engineer — we reply within one business day.
office@serverinvest.com