

TECHNICAL DATASHEET

DIGITUS • SERVER RACKS

DIGITUS SOHO 12U 19" wall-mount cabinet, 540 × 400 mm (W × D), grey

12U wall mounting cabinet, SOHO, unmounted 595x540x400 mm, full glass front door, grey

SKU DN-19 12-U-S-1

12U

Digitus



HEIGHT

12U

LOAD CAPACITY

60 kg

EXTERNAL DIMENSIONS

595 × 540 × 400 mm

PRICE

On request

REQUEST A QUOTATION ONLINE

serverinvest.com/product/digitus-dn-19-12-u-s-1

01 Product overview

The DIGITUS SOHO 19-inch wall-mounting cabinets are supplied flat-packed to keep shipping costs down and assemble in a few steps using the included instructions. Two pairs of depth-adjustable galvanized 19-inch rails, cable entries with brush strip in the roof and cover in the base, and ventilation slots for passive or active cooling are standard.

This 12U model (part number DN-19 12-U-S-1) measures 595 × 540 × 400 mm (H × W × D) and is finished in light grey (RAL 7035) electrostatic powder coating. It is equipped with a lockable safety-glass front door. The 19-inch mounting rails accept equipment with an installation depth of 170–270 mm. Rated load capacity is 60 kg. It is delivered flat-packed for self-assembly.

SOHO cabinets are designed for small and medium networks in offices, shops, practices and homes, where a compact lockable enclosure for a switch, patch panel, router and small UPS is needed.

HIGHLIGHTS

- 12U 19" network enclosure, 540 × 400 mm footprint
- Lockable safety-glass front door
- Equipment installation depth 170–270 mm
- Load capacity 60 kg
- IP20 protection, Light grey (RAL 7035)
- Flat-packed for easy transport and quick assembly

KEY SPECIFICATIONS

Manufacturer	DIGITUS (ASSMANN Electronic)
Part number	DN-19 12-U-S-1
EAN	4016032330967
Series	SOHO
Cabinet type	Wall mounting cabinet
Height (rack units)	12U
Mounting standard	483 mm (19")
External dimensions (H × W × D)	595 × 540 × 400 mm
Width	540 mm
Depth	400 mm
Height	595 mm
Load capacity	60 kg



02 Full specifications

GENERAL

Manufacturer	DIGITUS (ASSMANN Electronic)
Part number	DN-19 12-U-S-1
EAN	4016032330967
Series	SOHO
Cabinet type	Wall mounting cabinet
Height (rack units)	12U
Mounting standard	483 mm (19")

DIMENSIONS

External dimensions (H × W × D)	595 × 540 × 400 mm
---------------------------------	--------------------

Width	540 mm
Depth	400 mm
Height	595 mm

LOAD

Load capacity	60 kg
---------------	-------

DOORS & SECURITY

Front door	Glass door, single opening
Side panels	Both sides
Front door	Lockable safety-glass door
Door opening angle	200° door opening angle
Front door	1-point-locking-mechanism on the front door

CONSTRUCTION

Colour	Light grey (RAL 7035)
Material	1.1 - 1.5 strong sheet steel with a high loading capacity, powder coated

PROTECTION

IP rating	IP20
Protection class	Safety class rating IP20

DELIVERY

Delivery state	Unassembled (flat pack)
----------------	-------------------------

MOUNTING

19" rails	483 mm (19") profile rails mounted on the front- and rear side inside of the rack, galvanized
19" rails	483 mm (19") profile rails are adjustable in depth
Equipment mounting depth min.-max.	170-270 mm

CABLE MANAGEMENT

Cable entry	Cable entry with brush strip on the top and with plastic cover on the base
-------------	--

COOLING

Roof	Roof is prepared for fan units (punched out entries)
Ventilation	Ventilation slots for active and passive ventilation and exhausting

PACKAGE CONTENTS

Included	Installation set (screws, cage nuts, washers); 2 x keys; 1 x quick start guide
----------	--

LOGISTICS

Shipping weight	18.00 kg
-----------------	----------

03 Engineered, delivered & supported by ServerInvest

Engineering & sizing

Selected and sized against your real IT load, room and redundancy targets.

Installation

Delivery, installation and commissioning by our engineers across Europe.

Certified processes

ISO 9001, ISO 14001 and ISO 27001 certified project delivery.

Service & support

Maintenance, spare parts and support from a single partner.



Interested in this solution?

Request a quotation online or talk to a solutions engineer — we reply within one business day.
office@serverinvest.com

