

TECHNICAL DATASHEET

DIGITUS • SERVER RACKS

DIGITUS Dynamic Basic 12U 19" wall-mount cabinet, 600 × 600 mm (W × D), grey

12U wall mounting cabinet, Dynamic Basic 607x600x600 mm, color grey (RAL 7035)

SKU DN-19 12U-6/6-EC

12U

Digitus



HEIGHT

12U

LOAD CAPACITY

60 kg

EXTERNAL DIMENSIONS

607 × 600 × 600 mm

PRICE

On request

REQUEST A QUOTATION ONLINE

serverinvest.com/product/digitus-dn-19-12u-6-6-ec

01 Product overview

The DIGITUS Dynamic Basic wall-mounting cabinets are designed for simple, cost-optimised network expansion. Roof, base and rear panel feature pre-punched cable inlets, the roof is prepared for a fan module, and two pairs of depth-adjustable galvanized 19-inch rails with bidirectional U-markings are fitted inside.

This 12U model (part number DN-19 12U-6/6-EC) measures 607 × 600 × 600 mm (H × W × D) and is finished in light grey (RAL 7035) electrostatic powder coating. It is equipped with a lockable safety-glass front door. The 19-inch mounting rails accept equipment with an installation depth of 369–470 mm. Rated load capacity is 60 kg. It is delivered fully assembled.

Mounting is done in two steps with the supplied wall plate. Removable side panels and a lockable, removable glass front door give good access during installation. Dynamic Basic cabinets suit small offices, shops, branch sites and home networks that need a fully assembled, lockable 19-inch enclosure.

HIGHLIGHTS

- 12U 19" network enclosure, 600 × 600 mm footprint
- Lockable safety-glass front door
- Equipment installation depth 369–470 mm
- Load capacity 60 kg
- IP20 protection, Light grey (RAL 7035)
- Supplied fully assembled

KEY SPECIFICATIONS

Manufacturer	DIGITUS (ASSMANN Electronic)
Part number	DN-19 12U-6/6-EC
EAN	4016032221753
Series	Dynamic Basic (wall-mount)
Cabinet type	Wall mounting cabinet
Height (rack units)	12U
Mounting standard	483 mm (19")
External dimensions (H × W × D)	607 × 600 × 600 mm
Width	600 mm
Depth	600 mm
Height	607 mm
Load capacity	60 kg



02 Full specifications

GENERAL

Manufacturer	DIGITUS (ASSMANN Electronic)
Part number	DN-19 12U-6/6-EC
EAN	4016032221753
Series	Dynamic Basic (wall-mount)
Cabinet type	Wall mounting cabinet
Height (rack units)	12U
Mounting standard	483 mm (19")

DIMENSIONS

External dimensions (H × W × D)	607 × 600 × 600 mm
Width	600 mm
Depth	600 mm
Height	607 mm

LOAD

Load capacity	60 kg
---------------	-------

DOORS & SECURITY

Front door	Glass door, single opening
Side panels	Both sides
Front door	Lockable safety glass door with steel frame
Door opening angle	230° door opening angle
Front door	1-point locking on the front door
Front door	4 earthing points (base, side panel and front door) with protective cap

CONSTRUCTION

Colour	Light grey (RAL 7035)
Material	1.0 - 1.2 mm robust sheet steel with high load-bearing capacity, powder-coated

PROTECTION

IP rating	IP20
Protection class	Protection class IP20

DELIVERY

Delivery state	Assembled
----------------	-----------

MOUNTING

19" rails	483 mm (19") profile rails mounted at the front and rear inside the enclosure, galvanized
19" rails	483 mm (19") profile rails are adjustable in depth and marked with the height unit
Installation depth for components (standard maximum)	369 - 470 mm

CABLE MANAGEMENT

Cable entry	Cable entry possible at the rear, roof and base (pre-punched cut-outs)
-------------	--

COOLING

Roof	Roof is prepared to accommodate a fan element (punched-out mounts)
Ventilation	Ventilation slots for active and passive ventilation

PACKAGE CONTENTS

Included	Earthing cable set; Installation set (screws, cage nuts, washers); 2 x key
----------	--

LOGISTICS

Shipping weight

26.00 kg

03 Engineered, delivered & supported by ServerInvest

Engineering & sizing

Selected and sized against your real IT load, room and redundancy targets.

Installation

Delivery, installation and commissioning by our engineers across Europe.

Certified processes

ISO 9001, ISO 14001 and ISO 27001 certified project delivery.

Service & support

Maintenance, spare parts and support from a single partner.



Interested in this solution?

Request a quotation online or talk to a solutions engineer — we reply within one business day.
office@serverinvest.com

