TECHNICAL DATASHEET

DIGITUS · SERVER RACKS

DIGITUS SOHO Pro 9U 19" wall-mount cabinet, 540 × 400 mm (W × D), grey, perforated door

19" 9U wall mounting cabinet, SOHO Pro perforated door, 460 x 540 x 400 mm, unmounted, grey

SKU DN-49209 | 9U | Digitus

HEIGHT	LOAD CAPACITY	EXTERNAL DIMENSIONS	PRICE
9U	60 kg	460 × 540 × 400 mm	On request

ISO 9001 · ISO 14001 · ISO 27001 · cisco · tp-link · Omada by tp-link

REQUEST A QUOTATION ONLINE
serverinvest.com/product/digitus-dn-49209

01 Product overview

The DIGITUS SOHO Pro series packs a 19-inch network installation into a compact wall enclosure for homes, offices and space-constrained sub-distribution points. Two pairs of depth-adjustable galvanized rails with readable U-markings, cable entries in the roof and floor and ventilation slots are included, and the door hinges can be swapped to either side.

This 9U model (part number DN-49209) measures 460 × 540 × 400 mm (H × W × D) and is finished in light grey (RAL 7035) electrostatic powder coating. It is equipped with a perforated steel front door. The 19-inch mounting rails accept equipment with an installation depth of 319.25 mm. Rated load capacity is 60 kg. It is delivered flat-packed for self-assembly.

SOHO Pro cabinets ship flat-packed and are assembled in a few steps with the step-by-step guide. They are a good fit for small business networks, home labs, smart-home installations and branch offices.

KEY SPECIFICATIONS

Manufacturer	**DIGITUS (ASSMANN Electronic)**
Part number	**DN-49209**
EAN	**4016032499039**
Series	**SOHO Pro**
Cabinet type	**Wall mounting cabinet**
Height (rack units)	**9U**
Mounting standard	**483 mm (19")**
External dimensions (H × W × D)	**460 × 540 × 400 mm**
Width	**540 mm**
Depth	**400 mm**
Height	**460 mm**
Load capacity	**60 kg**

HIGHLIGHTS

- 9U 19" network enclosure, 540 × 400 mm footprint
- Perforated steel front door
- Equipment installation depth 319.25 mm
- Load capacity 60 kg
- IP20 protection, Light grey (RAL 7035)
- Flat-packed for easy transport and quick assembly

02 Full specifications

GENERAL	
Manufacturer	DIGITUS (ASSMANN Electronic)
Part number	DN-49209
EAN	4016032499039
Series	SOHO Pro
Cabinet type	Wall mounting cabinet
Height (rack units)	9U
Mounting standard	483 mm (19")

DIMENSIONS

External dimensions (H × W × D)	460 × 540 × 400 mm
Width	540 mm
Depth	400 mm
Height	460 mm

LOAD

Load capacity	60 kg

DOORS & SECURITY

Front door	Steel door, perforated, single opening
Side panels	Both sides
Front door	Lockable safety glass door, type 9473
Door opening angle	200° door opening angle
Front door	1-point locking on the front door

CONSTRUCTION

Colour	Light grey (RAL 7035)
Material	1.1 - 1.5 thick sheet steel with a high load-bearing capacity, powder-coated

PROTECTION

IP rating	IP20
Protection class	Protection class IP20

DELIVERY

Delivery state	Unassembled (flat pack)

MOUNTING

19" rails	483 mm (19") profile rails mounted at the front and rear inside the enclosure, galvanized
19" rails	483 mm (19") profile rails are adjustable in depth
Installation depth for components max.	319.25 mm

CABLE MANAGEMENT

Cable entry	Cable entry with plastic cover in the roof and floor

COOLING

Ventilation	Ventilation slots for active and passive ventilation

PACKAGE CONTENTS

Included	2x key; 1x QIG

LOGISTICS

Shipping weight	12.00 kg

03 Engineered, delivered & supported by ServerInvest

Engineering & sizing
Selected and sized against your real IT load, room and redundancy targets.

Installation
Delivery, installation and commissioning by our engineers across Europe.

Certified processes
ISO 9001, ISO 14001 and ISO 27001 certified project delivery.

Service & support
Maintenance, spare parts and support from a single partner.

Interested in this solution?

Request a quotation online or talk to a solutions engineer — we reply within one business day.
office@serverinvest.com