TECHNICAL DATASHEET

EXTRALINK · SERVER RACKS

# Extralink AZH 9U 600 mm × 600 mm double-section (swing) wall-mount cabinet, glass door, grey

9U wall-mount cabinet, 600 × 600 mm, 505 mm high

SKU EX.12950 | 9U | Extralink

| HEIGHT IN U | EXTERNAL DIMENSIONS | MANUFACTURER | PRICE |
|---|---|---|---|
| 9U | 505 × 600 × 600 mm | Extralink | On request |

REQUEST A QUOTATION ONLINE

serverinvest.com/product/extralink-ex-12950

## 01 Product overview

The Extralink EX.12950 is a 9U 19-inch wall-mount cabinet finished in grey, measuring 505 mm high, 600 mm wide and 600 mm deep. It is intended for offices, small server and network rooms, CCTV control rooms and other technical spaces where switches, patch panels, recorders and compact network equipment need a tidy, lockable enclosure that does not occupy floor space. Its double-section (swing-frame) design lets the front section pivot away from the wall-mounted rear part, giving convenient access to the rear of installed equipment and to incoming cabling.

The welded frame and outer walls are made of cold-rolled steel sheet. The front door is fitted with a tempered-glass pane, can be hung to open to the left or right and swings beyond 180°, so equipment remains visible while the cabinet stays closed. The side panels are held by latches and can be removed for installation and maintenance work, with locks and keys included.

Vertical rails are clearly marked with U positions. Cable openings are provided in both the top cover and the bottom panel, and the roof is prepared for mounting two fans to improve heat removal from active equipment. The cabinet is designed primarily for wall installation but can also be set up standing, and the frame concept allows straightforward self-assembly while keeping the package compact for transport.

### KEY SPECIFICATIONS

| | |
|---|---|
| Manufacturer | **Extralink** |
| Model | **EX.12950** |
| Series | **AZH double-section wall-mount cabinet** |
| Rack type | **Wall-mount cabinet** |
| Height in U | **9U** |
| Rack standard | **19-inch** |
| External dimensions (H × W × D) | **505 × 600 × 600 mm** |
| Installation | **Wall mounting; can also be positioned standing** |
| Mounting rails | **Vertical rails with U-height marking** |
| Side panels | **Removable, latch-fixed, lockable** |
| Construction | **Double-section (swing) design for rear access** |
| Lock | **Locks with keys included** |

### HIGHLIGHTS

- 9U 19-inch wall-mount cabinet, 600 × 600 mm footprint
- Double-section swing frame for rear access
- Removable side panels on latches, locks and keys included
- Cable entries in the top cover and bottom panel
- Roof prepared for two fans





## 02 Full specifications

| GENERAL | |
|---|---|
| Manufacturer | Extralink |
| Model | EX.12950 |
| Series | AZH double-section wall-mount cabinet |
| Rack type | Wall-mount cabinet |

## DIMENSIONS

| | |
|---|---|
| Height in U | 9U |
| Rack standard | 19-inch |
| External dimensions (H × W × D) | 505 × 600 × 600 mm |

## MOUNTING

| | |
|---|---|
| Installation | Wall mounting; can also be positioned standing |
| Mounting rails | Vertical rails with U-height marking |

## DOORS & PANELS

| | |
|---|---|
| Front door | Tempered-glass front door, reversible (left or right opening), opening angle over 180° |
| Side panels | Removable, latch-fixed, lockable |
| Construction | Double-section (swing) design for rear access |
| Lock | Locks with keys included |

## COOLING

| | |
|---|---|
| Fan provision | Roof prepared for 2 fans |

## CONSTRUCTION

| | |
|---|---|
| Frame | Welded frame, designed for easy self-assembly |
| Material | Cold-rolled steel sheet, tempered glass |
| Colour | Grey |
| Cable entry | Openings in top cover and bottom panel |

## 03 Engineered, delivered & supported by ServerInvest

### Engineering & sizing
Selected and sized against your real IT load, room and redundancy targets.

### Installation
Delivery, installation and commissioning by our engineers across Europe.

### Certified processes
ISO 9001, ISO 14001 and ISO 27001 certified project delivery.

### Service & support
Maintenance, spare parts and support from a single partner.

NATCERT ISO 9001 · NATCERT ISO 14001 · NATCERT ISO 27001 · cisco · tp-link · Omada by tp-link

## Interested in this solution?

Request a quotation online or talk to a solutions engineer — we reply within one business day.
office@serverinvest.com