TECHNICAL DATASHEET

EXTRALINK · SERVER RACKS

Extralink 42U 800 mm × 800 mm floor-standing rack cabinet, glass door, black

42U floor-standing cabinet, 800 × 800 mm, 1990 mm high

SKU EX.14459 | 42U | Extralink

HEIGHT IN U	EXTERNAL DIMENSIONS	MANUFACTURER	PRICE
42U	1990 × 800 × 800 mm	Extralink	On request

REQUEST A QUOTATION ONLINE

serverinvest.com/product/extralink-ex-14459

01 Product overview

The Extralink EX.14459 is a 42U 19-inch floor-standing rack cabinet in black with an 800 × 800 mm footprint and an overall height of 1990 mm. It is built for server rooms, network and telecom rooms, offices and CCTV control rooms that need a robust, lockable home for servers, switches, patch panels, storage and power equipment.

The outer walls are made of cold-rolled steel sheet. The front door has a tempered-glass pane and a key lock and can be mounted to open to either side; the cabinet is also closed with a steel rear door. Side panels are latch-mounted and removable to simplify installation and maintenance, and locks with keys are supplied.

Adjustable levelling feet and heavy-duty castors make it easy to position the cabinet and stand it securely on uneven floors. Cable entries in the top cover and bottom plate are adjustable, and a baying kit allows several cabinets to be joined into a row. The bottom panel offers eight cable pass-throughs, while the roof adds a ventilation outlet and two further cable entries.

HIGHLIGHTS

- 42U 19-inch floor-standing cabinet, 800 × 800 mm, 1990 mm high
- Tempered-glass front door with key lock, reversible
- Removable, lockable side panels
- Levelling feet and heavy-duty castors
- Adjustable cable entries top and bottom, baying kit for row installation

KEY SPECIFICATIONS

Manufacturer	**Extralink**
Model	**EX.14459**
Series	**Floor-standing rack cabinet**
Rack type	**Floor-standing enclosed cabinet**
Height in U	**42U**
Rack standard	**19-inch**
External dimensions (H × W × D)	**1990 × 800 × 800 mm**
Front door	**Tempered glass, key lock, left or right opening**
Rear door	**Steel**
Side panels	**Removable, latch-fixed, lockable**
Lock	**Locks with keys included**
Material	**Cold-rolled steel sheet, tempered glass**

02 Full specifications

GENERAL	
Manufacturer	Extralink
Model	EX.14459
Series	Floor-standing rack cabinet
Rack type	Floor-standing enclosed cabinet

DIMENSIONS	
Height in U	42U
Rack standard	19-inch
External dimensions (H × W × D)	1990 × 800 × 800 mm

DOORS & PANELS

Front door	Tempered glass, key lock, left or right opening
Rear door	Steel
Side panels	Removable, latch-fixed, lockable
Lock	Locks with keys included

CONSTRUCTION

Material	Cold-rolled steel sheet, tempered glass
Colour	Black
Cable entry	Adjustable cable entries in top cover and bottom plate; 8 pass-throughs in bottom panel, 2 in roof
Base	Adjustable levelling feet and heavy-duty castors
Baying	Baying kit for joining cabinets in a row

03 Engineered, delivered & supported by ServerInvest

Engineering & sizing
Selected and sized against your real IT load, room and redundancy targets.

Installation
Delivery, installation and commissioning by our engineers across Europe.

Certified processes
ISO 9001, ISO 14001 and ISO 27001 certified project delivery.

Service & support
Maintenance, spare parts and support from a single partner.

Interested in this solution?

Request a quotation online or talk to a solutions engineer — we reply within one business day.
office@serverinvest.com