

TECHNICAL DATASHEET

EXTRALINK · SERVER RACKS

Extralink EZDataCenter Enterprise 42U 600 × 1000 mm standing cabinet

42U integrated standing cabinet with active cooling, 600 × 1000 mm rack

SKU EX.35023

42U

Extralink



HEIGHT IN U

42U

MANUFACTURER

Extralink

MODEL

EX.35023

PRICE

On request

REQUEST A QUOTATION ONLINE

serverinvest.com/product/extralink-ex-35023

01 Product overview

The Extralink EZDataCenter Enterprise (EX.35023) is a 42U standing cabinet built around a 600 × 1000 mm rack and designed as an integrated, enclosed environment for IT equipment, with active cooling and monitoring built in. It suits edge sites, branch offices and small server rooms that need a self-contained enclosure rather than a dedicated, separately cooled room.

The enclosure combines a glass-and-steel front door with solid steel rear door and side panels; the rear door and side panels are removable, and key locks protect access to the installed equipment. The cabinet includes 19-inch mounting rails and sound-insulated construction with a stated noise level of 50 dB.

The listed maximum equipment load is 630 kg. The system operates from 110 - 240 V AC, 50/60 Hz, with a rated current of 10 A. The specified operating temperature range is -15 to 45 °C.

HIGHLIGHTS

- 42U integrated cabinet built on a 600 × 1000 mm rack
- Active cooling and built-in monitoring
- Glass/steel front door, removable steel rear door and side panels
- Sound-insulated, key-lockable enclosure
- Maximum load 630 kg



KEY SPECIFICATIONS

Manufacturer	Extralink
Model	EX.35023
Series	EZDataCenter Enterprise
Rack type	Standing integrated cabinet
Height in U	42U
Nominal rack size	600 × 1000 mm
Overall height	2000 mm
Mounting rails	19-inch rails included
Front door	Glass/steel
Rear door	Solid steel, removable
Side panels	Solid steel, removable
Lock	Key lock

02 Full specifications

GENERAL

Manufacturer	Extralink
Model	EX.35023
Series	EZDataCenter Enterprise
Rack type	Standing integrated cabinet

DIMENSIONS

Height in U	42U
Nominal rack size	600 × 1000 mm
Overall height	2000 mm

MOUNTING

Mounting rails	19-inch rails included
----------------	------------------------

DOORS & PANELS

Front door	Glass/steel
Rear door	Solid steel, removable
Side panels	Solid steel, removable
Lock	Key lock

LOAD

Maximum load	630 kg
--------------	--------

COOLING

Cooling	Active
Monitoring	Yes
Noise level	50 dB

CONSTRUCTION

Material	Galvanised steel, metal, glass, ABS
Colour	Blue / white
Soundproofing	Yes

ELECTRICAL

AC input voltage	110 - 240 V
Input frequency	50/60 Hz
Rated current	10 A

ENVIRONMENTAL

Operating temperature	-15 to 45 °C
-----------------------	--------------

03 Engineered, delivered & supported by ServerInvest

Engineering & sizing

Selected and sized against your real IT load, room and redundancy targets.

Installation

Delivery, installation and commissioning by our engineers across Europe.

Certified processes

ISO 9001, ISO 14001 and ISO 27001 certified project delivery.

Service & support

Maintenance, spare parts and support from a single partner.



Interested in this solution?

Request a quotation online or talk to a solutions engineer — we reply within one business day.
office@serverinvest.com

