TECHNICAL DATASHEET

EXTRALINK · SERVER RACKS

Extralink Premium 6U 600 mm × 450 mm tool-free wall-mount rack cabinet, glass door, grey

6U Premium wall-mount cabinet, 600 × 450 mm, 70 kg load

SKU EX.39298 | 6U | Extralink

HEIGHT IN U	MANUFACTURER	MODEL	PRICE
6U	Extralink	EX.39298	On request

REQUEST A QUOTATION ONLINE

serverinvest.com/product/extralink-ex-39298

01 Product overview

The Extralink Premium EX.39298 is a 6U 19-inch wall-mount cabinet in grey with a 600 mm width and 450 mm depth, aimed at installers who want a flexible, good-looking enclosure for network, CCTV and small server installations. It combines adjustable 19-inch rails, tool-free assembly and configurable ventilation in a sturdy, powder-coated DC01 steel body.

Assembly relies on removable snap fasteners, so the cabinet can be put together and taken apart without tools, and the removable housing gives full access to the interior while equipment is being installed. Both pairs of 19-inch rails can be repositioned in 30 mm steps over the full depth, and cut-outs in the frame make rail mounting more ergonomic.

Brush cable entries allow cabling to be routed in directly along the wall, and the cabinet accepts up to four 120 mm fans (two at the top and two at the bottom) for effective heat removal. The glazed front door uses a spring hinge and can be mounted on the left or right, and it is secured by Extralink's own high-security lock. The cabinet is prepared for wall mounting and carries up to 70 kg of equipment.

HIGHLIGHTS

- 6U 19-inch wall-mount cabinet, 600 × 450 mm
- Tool-free assembly with removable snap fasteners
- Rails adjustable in 30 mm steps over the full depth
- Brush cable entries, room for up to four 120 mm fans
- Glass door with spring hinge, reversible, high-security lock
- Maximum load 70 kg

KEY SPECIFICATIONS

Manufacturer	**Extralink**
Model	**EX.39298**
Series	**Extralink Premium**
Rack type	**Wall-mount cabinet**
Height in U	**6U**
Rack standard	**19-inch**
Width × depth	**600 × 450 mm**
Installation	**Wall mounting (frame holes for hanging and fixing)**
Front door	**Glass, spring hinge, left or right mounting**
Lock	**Extralink high-security lock**
Housing	**Removable for full interior access**
Maximum load	**70 kg**

02 Full specifications

GENERAL	
Manufacturer	Extralink
Model	EX.39298
Series	Extralink Premium
Rack type	Wall-mount cabinet

DIMENSIONS	
Height in U	6U
Rack standard	19-inch
Width × depth	600 × 450 mm

MOUNTING	
Mounting rails	2 pairs of adjustable 19-inch rails, repositionable every 30 mm over the full depth
Installation	Wall mounting (frame holes for hanging and fixing)

DOORS & PANELS

Front door	Glass, spring hinge, left or right mounting
Lock	Extralink high-security lock
Housing	Removable for full interior access

LOAD

Maximum load	70 kg

COOLING

Fan provision	Up to 4 × 120 mm fans (2 top, 2 bottom)

CONSTRUCTION

Material	DC01 steel sheet, powder-coated; glass door
Colour	Grey
Assembly	Tool-free, removable snap fasteners
Cable entry	Brush cable entries

03 Engineered, delivered & supported by ServerInvest

Engineering & sizing
Selected and sized against your real IT load, room and redundancy targets.

Installation
Delivery, installation and commissioning by our engineers across Europe.

Certified processes
ISO 9001, ISO 14001 and ISO 27001 certified project delivery.

Service & support
Maintenance, spare parts and support from a single partner.

Interested in this solution?

Request a quotation online or talk to a solutions engineer — we reply within one business day.
office@serverinvest.com