

TECHNICAL DATASHEET

EXTRALINK • SERVER RACKS

Extralink Premium 15U 600 mm × 600 mm tool-free wall-mount rack cabinet, glass door, black

15U Premium wall-mount cabinet, 600 × 600 mm, 70 kg load

SKU EX.39397

15U

Extralink



HEIGHT IN U

15U

MANUFACTURER

Extralink

MODEL

EX.39397

PRICE

On request**REQUEST A QUOTATION ONLINE**serverinvest.com/product/extralink-ex-39397

01 Product overview

The Extralink Premium EX.39397 is a 15U 19-inch wall-mount cabinet in black with a 600 mm width and 600 mm depth, aimed at installers who want a flexible, good-looking enclosure for network, CCTV and small server installations. It combines adjustable 19-inch rails, tool-free assembly and configurable ventilation in a sturdy, powder-coated DC01 steel body.

Assembly relies on removable snap fasteners, so the cabinet can be put together and taken apart without tools, and the removable housing gives full access to the interior while equipment is being installed. Both pairs of 19-inch rails can be repositioned in 30 mm steps over the full depth, and cut-outs in the frame make rail mounting more ergonomic.

Brush cable entries allow cabling to be routed in directly along the wall, and the cabinet accepts up to four 120 mm fans (two at the top and two at the bottom) for effective heat removal. The glazed front door uses a spring hinge and can be mounted on the left or right, and it is secured by Extralink's own high-security lock. The cabinet is prepared for wall mounting and carries up to 70 kg of equipment.

HIGHLIGHTS

- 15U 19-inch wall-mount cabinet, 600 × 600 mm
- Tool-free assembly with removable snap fasteners
- Rails adjustable in 30 mm steps over the full depth
- Brush cable entries, room for up to four 120 mm fans
- Glass door with spring hinge, reversible, high-security lock
- Maximum load 70 kg



KEY SPECIFICATIONS

Manufacturer	Extralink
Model	EX.39397
Series	Extralink Premium
Rack type	Wall-mount cabinet
Height in U	15U
Rack standard	19-inch
Width × depth	600 × 600 mm
Installation	Wall mounting (frame holes for hanging and fixing)
Front door	Glass, spring hinge, left or right mounting
Lock	Extralink high-security lock
Housing	Removable for full interior access
Maximum load	70 kg

02 Full specifications

GENERAL

Manufacturer	Extralink
Model	EX.39397
Series	Extralink Premium
Rack type	Wall-mount cabinet

DIMENSIONS

Height in U	15U
Rack standard	19-inch

Width × depth 600 × 600 mm

MOUNTING

Mounting rails 2 pairs of adjustable 19-inch rails, repositionable every 30 mm over the full depth

Installation Wall mounting (frame holes for hanging and fixing)

DOORS & PANELS

Front door Glass, spring hinge, left or right mounting

Lock Extralink high-security lock

Housing Removable for full interior access

LOAD

Maximum load 70 kg

COOLING

Fan provision Up to 4 × 120 mm fans (2 top, 2 bottom)

CONSTRUCTION

Material DC01 steel sheet, powder-coated; glass door

Colour Black

Assembly Tool-free, removable snap fasteners

Cable entry Brush cable entries

03 Engineered, delivered & supported by ServerInvest

Engineering & sizing

Selected and sized against your real IT load, room and redundancy targets.

Installation

Delivery, installation and commissioning by our engineers across Europe.

Certified processes

ISO 9001, ISO 14001 and ISO 27001 certified project delivery.

Service & support

Maintenance, spare parts and support from a single partner.



Interested in this solution?

Request a quotation online or talk to a solutions engineer — we reply within one business day.
office@serverinvest.com

