TECHNICAL DATASHEET

EXTRALINK · SERVER RACKS

Extralink 4U 600 mm × 600 mm wall-mount rack cabinet, glass door, grey

4U wall-mount cabinet, 600 × 600 mm, 280 mm high

SKU EX.8543 | 4U | Extralink

HEIGHT IN U	EXTERNAL DIMENSIONS	MANUFACTURER	PRICE
4U	280 × 600 × 600 mm	Extralink	On request

ISO 9001 · ISO 14001 · ISO 27001 · cisco · tp-link · Omada by tp-link

REQUEST A QUOTATION ONLINE

serverinvest.com/product/extralink-ex-8543

01 Product overview

The Extralink EX.8543 is a 4U 19-inch wall-mount cabinet finished in grey, measuring 280 mm high, 600 mm wide and 600 mm deep. It is intended for offices, small server and network rooms, CCTV control rooms and other technical spaces where switches, patch panels, recorders and compact network equipment need a tidy, lockable enclosure that does not occupy floor space.

The welded frame and outer walls are made of cold-rolled steel sheet. The front door is fitted with a tempered-glass pane, can be hung to open to the left or right and swings beyond 180°, so equipment remains visible while the cabinet stays closed. The side panels are held by latches and can be removed for installation and maintenance work, with locks and keys included.

Vertical rails are clearly marked with U positions. Cable openings are provided in both the top cover and the bottom panel, and the roof is prepared for mounting two fans to improve heat removal from active equipment. The cabinet is designed primarily for wall installation but can also be set up standing, and the frame concept allows straightforward self-assembly while keeping the package compact for transport.

KEY SPECIFICATIONS

Manufacturer	**Extralink**
Model	**EX.8543**
Series	**Wall-mount rack cabinet**
Rack type	**Wall-mount cabinet**
Height in U	**4U**
Rack standard	**19-inch**
External dimensions (H × W × D)	**280 × 600 × 600 mm**
Installation	**Wall mounting; can also be positioned standing**
Mounting rails	**Vertical rails with U-height marking**
Side panels	**Removable, latch-fixed, lockable**
Lock	**Locks with keys included**
Fan provision	**Roof prepared for 2 fans**

HIGHLIGHTS

- 4U 19-inch wall-mount cabinet, 600 × 600 mm footprint
- Reversible tempered-glass front door, opening beyond 180°
- Removable side panels on latches, locks and keys included
- Cable entries in the top cover and bottom panel
- Roof prepared for two fans



02 Full specifications

GENERAL	
Manufacturer	Extralink
Model	EX.8543
Series	Wall-mount rack cabinet
Rack type	Wall-mount cabinet

DIMENSIONS	
Height in U	4U

Rack standard	19-inch
External dimensions (H × W × D)	280 × 600 × 600 mm

MOUNTING

Installation	Wall mounting; can also be positioned standing
Mounting rails	Vertical rails with U-height marking

DOORS & PANELS

Front door	Tempered-glass front door, reversible (left or right opening), opening angle over 180°
Side panels	Removable, latch-fixed, lockable
Lock	Locks with keys included

COOLING

Fan provision	Roof prepared for 2 fans

CONSTRUCTION

Frame	Welded frame, designed for easy self-assembly
Material	Cold-rolled steel sheet, tempered glass
Colour	Grey
Cable entry	Openings in top cover and bottom panel

03 Engineered, delivered & supported by ServerInvest

Engineering & sizing
Selected and sized against your real IT load, room and redundancy targets.

Installation
Delivery, installation and commissioning by our engineers across Europe.

Certified processes
ISO 9001, ISO 14001 and ISO 27001 certified project delivery.

Service & support
Maintenance, spare parts and support from a single partner.

NATCERT ISO 9001 · NATCERT ISO 14001 · NATCERT ISO 27001 · CISCO · tp-link · Omada by tp-link

Interested in this solution?

Request a quotation online or talk to a solutions engineer — we reply within one business day.
office@serverinvest.com