TECHNICAL DATASHEET

EXTRALINK · SERVER RACKS

# Extralink 9U 600 mm × 450 mm wall-mount rack cabinet, glass door, grey

9U wall-mount cabinet, 600 × 450 mm, 498 mm high

SKU EX.8574 | 9U | Extralink

| HEIGHT IN U | EXTERNAL DIMENSIONS | MANUFACTURER | PRICE |
|---|---|---|---|
| 9U | 498 × 600 × 450 mm | Extralink | On request |

ISO 9001 · ISO 14001 · ISO 27001 · cisco · tp-link · Omada by tp-link

REQUEST A QUOTATION ONLINE

serverinvest.com/product/extralink-ex-8574

## 01 Product overview

The Extralink EX.8574 is a 9U 19-inch wall-mount cabinet finished in grey, measuring 498 mm high, 600 mm wide and 450 mm deep. It is intended for offices, small server and network rooms, CCTV control rooms and other technical spaces where switches, patch panels, recorders and compact network equipment need a tidy, lockable enclosure that does not occupy floor space.

The welded frame and outer walls are made of cold-rolled steel sheet. The front door is fitted with a tempered-glass pane, can be hung to open to the left or right and swings beyond 180°, so equipment remains visible while the cabinet stays closed. The side panels are held by latches and can be removed for installation and maintenance work, with locks and keys included.

Vertical rails are clearly marked with U positions. Cable openings are provided in both the top cover and the bottom panel, and the roof is prepared for mounting two fans to improve heat removal from active equipment. The cabinet is designed primarily for wall installation but can also be set up standing, and the frame concept allows straightforward self-assembly while keeping the package compact for transport.

### KEY SPECIFICATIONS

| | |
|---|---|
| Manufacturer | **Extralink** |
| Model | **EX.8574** |
| Series | **Wall-mount rack cabinet** |
| Rack type | **Wall-mount cabinet** |
| Height in U | **9U** |
| Rack standard | **19-inch** |
| External dimensions (H × W × D) | **498 × 600 × 450 mm** |
| Installation | **Wall mounting; can also be positioned standing** |
| Mounting rails | **Vertical rails with U-height marking** |
| Side panels | **Removable, latch-fixed, lockable** |
| Lock | **Locks with keys included** |
| Fan provision | **Roof prepared for 2 fans** |

### HIGHLIGHTS

- 9U 19-inch wall-mount cabinet, 600 × 450 mm footprint
- Reversible tempered-glass front door, opening beyond 180°
- Removable side panels on latches, locks and keys included
- Cable entries in the top cover and bottom panel
- Roof prepared for two fans

## 02 Full specifications

| GENERAL | |
|---|---|
| Manufacturer | Extralink |
| Model | EX.8574 |
| Series | Wall-mount rack cabinet |
| Rack type | Wall-mount cabinet |

| DIMENSIONS | |
|---|---|
| Height in U | 9U |

| | |
|---|---|
| Rack standard | 19-inch |
| External dimensions (H × W × D) | 498 × 600 × 450 mm |

## MOUNTING

| | |
|---|---|
| Installation | Wall mounting; can also be positioned standing |
| Mounting rails | Vertical rails with U-height marking |

## DOORS & PANELS

| | |
|---|---|
| Front door | Tempered-glass front door, reversible (left or right opening), opening angle over 180° |
| Side panels | Removable, latch-fixed, lockable |
| Lock | Locks with keys included |

## COOLING

| | |
|---|---|
| Fan provision | Roof prepared for 2 fans |

## CONSTRUCTION

| | |
|---|---|
| Frame | Welded frame, designed for easy self-assembly |
| Material | Cold-rolled steel sheet, tempered glass |
| Colour | Grey |
| Cable entry | Openings in top cover and bottom panel |

## 03 Engineered, delivered & supported by ServerInvest

### Engineering & sizing
Selected and sized against your real IT load, room and redundancy targets.

### Installation
Delivery, installation and commissioning by our engineers across Europe.

### Certified processes
ISO 9001, ISO 14001 and ISO 27001 certified project delivery.

### Service & support
Maintenance, spare parts and support from a single partner.

NATCERT ISO 9001 · NATCERT ISO 14001 · NATCERT ISO 27001 · CISCO · tp-link · Omada by tp-link

## Interested in this solution?

Request a quotation online or talk to a solutions engineer — we reply within one business day.
office@serverinvest.com