

TECHNICAL DATASHEET

FIBRAIN • SERVER RACKS

FIBRAIN SRS 45U 800 mm × 1000 mm floor-standing network cabinet, glass door, black RAL 9005

45U floor-standing cabinet, 800 × 1000 mm, glass door, 1360 kg load

SKU SRS-45-8/10-S04-B

45U

Fibrain



HEIGHT IN U

45U

MANUFACTURER

FIBRAIN

MODEL

SRS-45-8/10-S04-B

PRICE

On request

REQUEST A QUOTATION ONLINE

serverinvest.com/product/fibrain-srs-45-8-10-s04-b

01 Product overview

The FIBRAIN SRS-45-8/10-S04-B is a 45U floor-standing network cabinet from the FIBRAIN DATA range, 800 mm wide and 1000 mm deep, finished in black RAL 9005. It is designed for indoor installations such as server rooms, telecom rooms and building distributors, and can be combined with neighbouring cabinets into rows or a Data Box arrangement.

The front door combines a glass panel with metal sides and is closed by a three-point rod-latch lock with swing handle; it opens up to 180° and its opening direction can be changed. At the rear, a shortened solid steel door with single-point lock is complemented by a 3U panel with a brush strip below it for cable entry. Solid steel side panels have single-point locks, and two pairs of 19-inch mounting profiles with U marking carry the equipment.

Top and bottom plates feature 71 mm wide cable openings, wide enough for a power cable with a three-phase plug, all closed by knock-out blanking plates. The cabinet can stand directly on the floor with no protruding elements underneath, and on levelling feet it achieves IP20 to EN 60529 (excluding brush entries). FIBRAIN rates it for 1360 kg of equipment on levelling feet or a plinth; an earthing bar and earthing cables are included.

HIGHLIGHTS

- 45U 19-inch floor-standing cabinet, 800 × 1000 mm
- Glass front door with three-point rod-latch lock and swing handle
- Shortened steel rear door plus 3U brush-strip panel
- 71 mm cable openings top and bottom with knock-out plates
- Load capacity 1360 kg on levelling feet or plinth
- IP20 (EN 60529), earthing bar and cables included



KEY SPECIFICATIONS

Manufacturer	FIBRAIN
Model	SRS-45-8/10-S04-B
Product line	FIBRAIN DATA
Series	SRS floor-standing cabinet
Rack type	Floor-standing network cabinet
Height in U	45U
Width × depth	800 × 1000 mm
Mounting profiles	2 pairs of 19-inch profiles with U marking (Al-Zn coated)
Rear door	Solid steel, shortened, single-point lock, plus 3U brush-strip panel
Side panels	Solid steel, single-point locks
Load on levelling feet / plinth	1360 kg
Load on castors	Type 150: 150 kg; type 300: 500 kg

02 Full specifications

GENERAL

Manufacturer	FIBRAIN
Model	SRS-45-8/10-S04-B
Product line	FIBRAIN DATA
Series	SRS floor-standing cabinet
Rack type	Floor-standing network cabinet

DIMENSIONS

Height in U	45U
Width × depth	800 × 1000 mm

MOUNTING

Mounting profiles	2 pairs of 19-inch profiles with U marking (Al-Zn coated)
-------------------	---

DOORS & PANELS

Front door	Glass with metal sides, three-point rod-latch lock with swing handle, 180° opening, reversible
Rear door	Solid steel, shortened, single-point lock, plus 3U brush-strip panel
Side panels	Solid steel, single-point locks

LOAD

Load on levelling feet / plinth	1360 kg
Load on castors	Type 150: 150 kg; type 300: 500 kg

CONSTRUCTION

Material	Sheet steel; mineral safety glass; zamak outriggers
Colour	Black RAL 9005
Cable entry	71 mm wide openings in top and bottom plates, knock-out blanking plates
Base	Levelling feet; can stand directly on the floor
Grounding	Earthing bar and cables
Baying	Can be joined into rows / Data Box

COMPLIANCE

IP rating	IP20 (EN 60529) on levelling feet, excluding brush entries
-----------	--

03 Engineered, delivered & supported by ServerInvest

Engineering & sizing

Selected and sized against your real IT load, room and redundancy targets.

Installation

Delivery, installation and commissioning by our engineers across Europe.

Certified processes

ISO 9001, ISO 14001 and ISO 27001 certified project delivery.

Service & support

Maintenance, spare parts and support from a single partner.



Interested in this solution?

Request a quotation online or talk to a solutions engineer — we reply within one business day.
office@serverinvest.com

