

TECHNICAL DATASHEET

SUPERMICRO • STORAGE SERVERS

Supermicro 2U UP Storage Server SSG-520P-ACTR12H

2U UP front-loading storage server with 12 direct-attached hot-swap 3.5" SAS/
SATA bays (SAS hardware RAID) and PCIe 4.0

SKU SSG-520P-ACTR12H

2U

LGA4189

Supermicro



FORM FACTOR

2U

MAX POWER (BASE)

333 W

HEAT OUTPUT

1,136 BTU/h

PRICE

On request

REQUEST A QUOTATION ONLINE

serverinvest.com/product/ssg-520p-actr12h

01 Product overview

The Supermicro SSG-520P-ACTR12H is a 2U UP Storage Server built on Intel Xeon Scalable 3rd Gen with up to 2 TB of memory in 8 DIMM slots.

2U UP front-loading storage server with 12 direct-attached hot-swap 3.5" SAS/SATA bays (SAS hardware RAID) and PCIe 4.0.


ServerInvest configures every SSG-520P-ACTR12H to order, updates BIOS and BMC firmware, installs your operating system on request and runs a 48-hour burn-in test before delivery. Every system includes a 3-year warranty.

HIGHLIGHTS

- Intel Xeon Scalable 3rd Gen
- Up to 2 TB memory · 8 DIMM slots
- Total 12 bays 12 front hot-swap 3.5" SAS/SATA drive bays
- Power: 2x 800W
- Networking: 2 RJ45 10GbE with Intel X550

KEY SPECIFICATIONS


Form factor	2U
Processor	Intel Xeon Scalable 3rd Gen
Socket	LGA4189
Memory	8 DIMM slots, up to 2 TB
Drive bays	28 (28 NVMe)
Power supply	2× 800 W
Typical power draw	450 W
Networking	2 RJ45 10GbE with Intel X550
Dimensions (W×H×D)	437 × 89 mm



02 Power & thermal

Calculated for the base configuration

IDLE	TYPICAL	MAXIMUM	HEAT (MAX)	COOLING	PSU LOAD
86 W	210 W	333 W	1,136 BTU/h	0.3 kW	42%



Typical 210 W · max 333 W · single PSU rating 800 W


Annual IT energy (24/7)	1,514 kWh
Annual facility energy (PUE 1.5)	2,271 kWh
Annual energy cost	€303 IT · €454 incl. cooling (at 0.20 €/kWh)
CO ₂ emissions / year	0.59 t (grid factor 0.26 kg/kWh)
Power supplies	2× 800 W redundant (N+1)

POWER BY COMPONENT	IDLE	TYPICAL	MAX
Chassis, motherboard, fans, BMC	50 W	77 W	110 W
CPU (base configuration)	25 W	110 W	185 W
2× Memory (base configuration)	6 W	10 W	18 W

DC loads converted to wall power at 94% PSU efficiency; typical load assumed 70% of the time. Engineering estimates — confirm with the manufacturer's power calculator for critical designs.

03 Power connection diagram

Dual-feed (A/B) connection for redundant power supplies



- Connect PSU 1 to PDU-A and PSU 2 to PDU-B (independent feeds) using IEC C13/C14 (10 A) power cords.
- Maximum current per feed: 1.5 A at 230 V — each feed must be able to carry the full load if the other fails.
- Recommended protection per PDU circuit: MCB 6 A, curve C; RCD according to local regulations.
- Heat to remove at full load: 333 W = 1,136 BTU/h (0.3 kW).

04 Full specifications

MOTHERBOARD

Super X12SPi-TF

PROCESSOR

CPU	Single Socket P+ (LGA-4189) 3rd Gen Intel Xeon Scalable processors
Core Count	Up to 40C/80T; Up to 60MB Cache
Note	Supports up to 270W TDP CPUs (Air Cooled)

SYSTEM MEMORY

Memory	Slot Count: 8 DIMM slots Max Memory (1DPC): Up to 2TB 3200MT/s ECC DDR4 RDIMM/LRDIMM Supports Intel Optane persistent memory 200 series View Memory Options
Memory Voltage	1.2V

ON-BOARD DEVICES

SAS	SAS (12Gbps) via Broadcom 3916; RAID 0/1/5/6/10/50/60 support
NVMe	NVMe; RAID 0/1 support(Intel VROC RAID key required) View NVMe Options
Network Connectivity	2 RJ45 10GbE with Intel X550 View AOC Options

INPUT / OUTPUT

LAN	2 RJ45 10 GbE LAN ports (Intel X550) 1 RJ45 1 GbE Dedicated BMC LAN port (IPMI shared on LAN port 1)
-----	---

USB	2 USB 2.0 ports (header) 2 USB 3.2 Gen1 Type-A ports (rear) 2 USB 2.0 Type-A ports (rear) 2 USB 3.2 Gen1 ports (Header) 1 USB 3.2 Gen1 Type-A port
Video	1 VGA port
Serial	1 COM port (Header)
DOM	2 Super DOM (Disk on Module) portswith built-in power
TPM	1 TPM header

SYSTEM BIOS

BIOS Type	AMI 32MB SPI Flash EEPROM
-----------	---------------------------

MANAGEMENT

Software	SuperCloud Composer (SCC) Supermicro Server Manager (SSM) Supermicro Update Manager (SUM) Supermicro SuperDoctor 5 (SD5) Super Diagnostics Offline (SDO) Supermicro Thin-Agent Service (TAS) SuperServer Automation Assistant (SAA) New!
Power configurations	ACPI/APM Power Management

SECURITY

Hardware	Trusted Platform Module (TPM) 2.0 Silicon Root of Trust (RoT) – NIST 800-193 Compliant
Features	Cryptographically Signed Firmware Secure Boot Secure Firmware Updates Automatic Firmware Recovery System Lockdown

PC HEALTH MONITORING

CPU	7+1 Phase-switching voltage regulator module (VRM) Monitors for CPU Cores, Chipset Voltages, Memory
Fan	Fans with tachometer monitoring Pulse Width Modulated (PWM) fan connectors Status monitor for speed control
Temperature	Monitoring for CPU and chassis environment Thermal Control for fan connectors

CERTIFICATIONS

Operating Systems	ESXi 6.7 U3, ESXi 7.0 U2, Oracle Linux 8.3, RHEL 8.2, Windows Server 2019, Windows Server 2022 View all OS Compatibility and Certification Matrix
-------------------	--

CHASSIS

Form Factor	2U Rackmount
Model	CSE-826BTS-R802LPB

DIMENSIONS AND WEIGHT

Height	3.5" (89 mm)
Width	17.2" (437 mm)
Depth	25.6" (650 mm)
Package	11.5" (H) x 26.5" (W) x 34" (D)
Weight	Gross Weight: 58 lbs (26.3 kg) Net Weight: 34 lbs (15.4 kg)
Available Color	Black

FRONT PANEL

Buttons	Power On/Off System Reset
LED	Device Activity LAN 1 Activity LAN 2 Activity Power Failure LED Power status System information

EXPANSION SLOTS

PCI-Express (PCIe) Configuration	Default 2 PCIe 4.0 x8 LP slots 2 PCIe 4.0 x16 LP slots View AOC Options
----------------------------------	--

DRIVE BAYS / STORAGE

Drive Bays Configuration	Default: Total 12 bays 12 front hot-swap 3.5" SAS/SATA drive bays Option A: Total 14 bays 12 front hot-swap 3.5" SAS/SATA drive bays 2 rear hot-swap 2.5" PCIe 4.0 NVMe*/SAS*/SATA* drive bays (*NVMe/SAS/SATA support may require additional storage controller and/or cables, please see the optional parts list for details) View NVMe Options View Drive Options
M.2	1 M.2 PCIe 3.0 x4 NVMe/SATA slot (M-key 2280/22110) View M.2 Options

SYSTEM COOLING

Fans	Up to 3 Heavy Duty PWM 80x80x38mm Fan(s)
Air Shroud	1 Air Shroud

POWER SUPPLY

2x 800W
2x 800W Redundant (1 + 1) Titanium Level (96%) power supplies
Dimension (WxHxL)
76 x 40 x 336 mm

OPERATING ENVIRONMENT

Environmental Spec.

Operating Temperature: 10°C to 35°C (50°F to 95°F)
Non-operating Temperature: -40°C to 70°C (-40°F to 158°F)
Operating Relative Humidity: 8% to 90% (non-condensing)
Non-operating Relative Humidity: 5% to 95% (non-condensing)

05 Built, tested & supported by ServerInvest

Engineered configuration

Every option validated for socket, memory channels, PCIe lanes, power and cooling.

48-hour burn-in

Assembled, firmware-updated and stress-tested before it leaves our workshop.

3-year warranty

Standard on every system, with on-site next-business-day upgrades available.

Rack-ready delivery

Rails, cable management and labelling included — delivered across Europe.



Interested in this solution?

Request a quotation online or talk to a solutions engineer — we reply within one business day.
office@serverinvest.com

Official manufacturer datasheet: serverinvest.com/product/ssg-520p-actr12h/datasheet/manufacture

