

TECHNICAL DATASHEET

SUPERMICRO • STORAGE SERVERS

Supermicro 2U Storage Server SSG-620P-E1CR24L

2U front/top-loading storage server with 24 hot-swap 3.5" SAS/SATA bays and PCIe 4.0

SKU SSG-620P-E1CR24L

2U

LGA4189

Supermicro



FORM FACTOR

2U

MAX POWER (BASE)

549 W

HEAT OUTPUT

1,873 BTU/h

PRICE

On request

REQUEST A QUOTATION ONLINE

serverinvest.com/product/ssg-620p-e1cr24l

01 Product overview

The Supermicro SSG-620P-E1CR24L is a 2U Storage Server built on dual Intel Xeon Scalable 3rd Gen processors with up to 4 TB of memory in 16 DIMM slots.

2U front/top-loading storage server with 24 hot-swap 3.5" SAS/SATA bays and PCIe 4.0.

ServerInvest configures every SSG-620P-E1CR24L to order, updates BIOS and BMC firmware, installs your operating system on request and runs a 48-hour burn-in test before delivery. Every system includes a 3-year warranty.

HIGHLIGHTS

- Dual Intel Xeon Scalable 3rd Gen
- Up to 4 TB memory · 16 DIMM slots
- Total 28 bays 12 front hot-swap 3.5" SAS/SATA drive bays
- Power: 2x 1600W
- Networking: Via AIOM

KEY SPECIFICATIONS


Form factor	2U
Processor	2× Intel Xeon Scalable 3rd Gen
Socket	LGA4189
Memory	16 DIMM slots, up to 4 TB
Drive bays	44 (44 NVMe)
Power supply	2× 1600 W
Typical power draw	750 W
Networking	Via AIOM
Dimensions (W×H×D)	437 × 89 mm



02 Power & thermal

Calculated for the base configuration

IDLE	TYPICAL	MAXIMUM	HEAT (MAX)	COOLING	PSU LOAD
119 W	337 W	549 W	1,873 BTU/h	0.5 kW	34%



Typical 337 W · max 549 W · single PSU rating 1600 W


Annual IT energy (24/7)	2,379 kWh
Annual facility energy (PUE 1.5)	3,569 kWh
Annual energy cost	€476 IT · €714 incl. cooling (at 0.20 €/kWh)
CO ₂ emissions / year	0.93 t (grid factor 0.26 kg/kWh)
Power supplies	2× 1600 W redundant (N+1)

POWER BY COMPONENT	IDLE	TYPICAL	MAX
Chassis, motherboard, fans, BMC	50 W	77 W	110 W
2× CPU (base configuration)	50 W	220 W	370 W
4× Memory (base configuration)	12 W	20 W	36 W

DC loads converted to wall power at 94% PSU efficiency; typical load assumed 70% of the time. Engineering estimates — confirm with the manufacturer's power calculator for critical designs.

03 Power connection diagram

Dual-feed (A/B) connection for redundant power supplies



- Connect PSU 1 to PDU-A and PSU 2 to PDU-B (independent feeds) using IEC C13/C14 (10 A) power cords.
- Maximum current per feed: 2.5 A at 230 V — each feed must be able to carry the full load if the other fails.
- Recommended protection per PDU circuit: MCB 6 A, curve C; RCD according to local regulations.
- Heat to remove at full load: 549 W = 1,873 BTU/h (0.5 kW).

04 Full specifications

MOTHERBOARD

Super X12DSC-A6

PROCESSOR

CPU	Dual Socket P+ (LGA-4189) 3rd Gen Intel Xeon Scalable processors
Core Count	Up to 38C/76T; Up to 57MB Cache per CPU
Note	Supports 120W - 205W TDP CPUs (Air Cooled)

SYSTEM MEMORY

Memory	Slot Count: 16 DIMM slots Max Memory (2DPC): Up to 4TB 3200MT/s ECC DDR4 RDIMM/LRDIMM View Memory Options
Memory Voltage	1.2V

ON-BOARD DEVICES

Network Connectivity	Via AIOM View AIOM Options View AOC Options
----------------------	---

INPUT / OUTPUT

LAN	1 RJ45 1 GbE Dedicated BMC LAN port
USB	2 USB 3.0 ports (rear)
Video	1 VGA port
DOM	2 Super DOM (Disk on Module) ports

SYSTEM BIOS

BIOS Type	AMI 128MB SPI Flash EEPROM
-----------	----------------------------

MANAGEMENT

Software	SuperCloud Composer (SCC) Supermicro Server Manager (SSM) Supermicro Update Manager (SUM) Supermicro SuperDoctor 5 (SD5) Super Diagnostics Offline (SDO) Supermicro Thin-Agent Service (TAS) SuperServer Automation Assistant (SAA) New!
----------	--

Power configurations	Power-on mode for AC power recovery ACPI Power Management
----------------------	--

SECURITY

Hardware	Trusted Platform Module (TPM) 2.0 Silicon Root of Trust (RoT) – NIST 800-193 Compliant
----------	---

Features	Cryptographically Signed Firmware Secure Boot Secure Firmware Updates Automatic Firmware Recovery System Lockdown
----------	---

PC HEALTH MONITORING

CPU	4+1 Phase-switching voltage regulator Monitors for CPU Cores, Chipset Voltages, Memory
-----	---

Fan	Fans with tachometer monitoring Pulse Width Modulated (PWM) fan connectors Status monitor for speed control
-----	---

Temperature	Monitoring for CPU and chassis environment Thermal Control for fan connectors
-------------	--

CHASSIS

Form Factor	2U Rackmount
-------------	--------------

Model	CSE-826STS-R1K62P1
-------	--------------------

DIMENSIONS AND WEIGHT

Height	3.5"
--------	------

Width	17.2"
-------	-------

Depth	34"
-------	-----

Package	12" (H) x 29" (W) x 52" (D)
---------	-----------------------------

Weight	Gross Weight: 74.5 lbs (33.79 kg) Net Weight: 52 lbs (23.59 kg)
--------	--

Available Color	Silver
-----------------	--------

FRONT PANEL

Buttons	Power On/Off
---------	--------------

LED	HDD activity Network activity Power status System information (overheat/UID)
-----	---

EXPANSION SLOTS

PCI-Express (PCIe) Configuration	Default 1 PCIe 4.0 x8 LP slot 2 PCIe 4.0 x16 LP slots 1 PCIe 4.0 x16 AIOM slot (OCP 3.0 compatible) View AOC Options
----------------------------------	--

DRIVE BAYS / STORAGE

Drive Bays Configuration	Default: Total 28 bays 12 front hot-swap 3.5" SAS/SATA drive bays 12 top-loading hot-swap 3.5" SAS/SATA drive bays 2 rear hot-swap 2.5" SATA drive bays 2 rear hot-swap 2.5" NVMe drive bays View NVMe Options View Drive Options
M.2	2 M.2 NVMe slots (M-key 2280/22110) View M.2 Options

SYSTEM COOLING

Fans	Up to 5 Heavy Duty 8cm Fan(s)
Air Shroud	1 Air Shroud

POWER SUPPLY

	2x 1600W 2x 1600W Redundant Titanium Level (96%) Hot-plug power supplies Dimension (WxHxL) 73.5 x 40 x 203 mm
--	--

OPERATING ENVIRONMENT

RoHS	RoHS Compliant
Environmental Spec.	Operating Temperature: 10°C to 35°C (50°F to 95°F) Non-operating Temperature: -40°C to 60°C (-40°F to 140°F) Operating Relative Humidity: 8% to 90% (Non-Condensing) Non-operating Relative Humidity: 5% to 95% (Non-Condensing)

05 Built, tested & supported by ServerInvest

Engineered configuration

Every option validated for socket, memory channels, PCIe lanes, power and cooling.

48-hour burn-in

Assembled, firmware-updated and stress-tested before it leaves our workshop.

3-year warranty

Standard on every system, with on-site next-business-day upgrades available.

Rack-ready delivery

Rails, cable management and labelling included — delivered across Europe.



Interested in this solution?

Request a quotation online or talk to a solutions engineer — we reply within one business day.
office@serverinvest.com

Official manufacturer datasheet: serverinvest.com/product/ssg-620p-e1cr24l/datasheet/manufactur

