

TECHNICAL DATASHEET

SUPERMICRO · RACKMOUNT SERVERS

Supermicro 1U Hyper Server SYS-122H-TN

1U Hyper with 8 hot-swap 2.5" NVMe/SAS/SATA bays and 3 PCIe 5.0 x16 + 1 PCIe 5.0 x16 AIOM slot

SKU SYS-122H-TN

1U

LGA4710

Supermicro



FORM FACTOR

1U

MAX POWER (BASE)

565 W

HEAT OUTPUT

1,928 BTU/h

PRICE

from €8,170**CONFIGURE & QUOTE ONLINE**serverinvest.com/product/sys-122h-tn

01 Product overview

The Supermicro SYS-122H-TN is a 1U Hyper Server built on dual Intel Xeon 6 processors with up to 8 TB of memory in 32 DIMM slots.

1U Hyper with 8 hot-swap 2.5" NVMe/SAS/SATA bays and 3 PCIe 5.0 x16 + 1 PCIe 5.0 x16 AIOM slot.

The chassis accepts up to 1 GPU accelerators for AI, rendering and HPC workloads.

ServerInvest configures every SYS-122H-TN to order, updates BIOS and BMC firmware, installs your operating system on request and runs a 48-hour burn-in test before delivery. Every system includes a 3-year warranty.

HIGHLIGHTS

- Dual Intel Xeon 6
- Up to 8 TB memory · 32 DIMM slots
- Total 8 bays 8 front hot-swap 2.5" NVMe*/SAS*/SATA* drive bays
- Up to 1 GPUs
- Power: 2x 1200W
- Networking: Via AIOM

KEY SPECIFICATIONS

Form factor	1U
Processor	2× Intel Xeon 6
Socket	LGA4710
Memory	32 DIMM slots, up to 8 TB
Memory type	DDR5-6400 ECC RDIMM
Drive bays	20 (20 NVMe)
GPU	Up to 1 GPUs
Power supply	2× 1200 W
Typical power draw	1200 W
Networking	Via AIOM
Dimensions (W×H×D)	437 × 44 mm



02 Base configuration

Components included in the listed base price — every part can be changed in the online configurator

COMPONENT	DESCRIPTION	QTY
Base system	Supermicro 1U Hyper Server SYS-122H-TN	1
Processor	Intel Xeon 6710E Processor 64 Cores (96M Cache, 2.40Ghz) 205W	2
Memory	16GB 6400MT/s DDR5 ECC Registered DIMM Module	4
Warranty & support	3-year return-to-base warranty (included)	1

Base configuration from

€8,170
excl. VAT

03 Power & thermal

Calculated for the base configuration

IDLE	TYPICAL	MAXIMUM	HEAT (MAX)	COOLING	PSU LOAD
119 W	367 W	565 W	1,928 BTU/h	0.6 kW	47%

Typical 367 W · max 565 W · single PSU rating 1200 W

Annual IT energy (24/7)	2,563 kWh
Annual facility energy (PUE 1.5)	3,845 kWh
Annual energy cost	€513 IT · €769 incl. cooling (at 0.20 €/kWh)
CO ₂ emissions / year	1.00 t (grid factor 0.26 kg/kWh)
Power supplies	2× 1200 W redundant (N+1)


POWER BY COMPONENT

	IDLE	TYPICAL	MAX
Chassis, motherboard, fans, BMC	38 W	59 W	85 W
2× CPU — Intel Xeon 6710E Processor 64 Cores	62 W	266 W	410 W
4× Memory 16 GB DIMM	12 W	20 W	36 W

DC loads converted to wall power at 94% PSU efficiency; typical load assumed 70% of the time. Engineering estimates — confirm with the manufacturer's power calculator for critical designs.

04 Power connection diagram

Dual-feed (A/B) connection for redundant power supplies



- Connect PSU 1 to PDU-A and PSU 2 to PDU-B (independent feeds) using IEC C13/C14 (10 A) power cords.
- Maximum current per feed: 2.6 A at 230 V — each feed must be able to carry the full load if the other fails.
- Recommended protection per PDU circuit: MCB 6 A, curve C; RCD according to local regulations.
- Heat to remove at full load: 565 W = 1,928 BTU/h (0.6 kW).

05 Full specifications

MOTHERBOARD

Super X14DBM-SP

PROCESSOR

CPU	Dual Socket E2 (LGA-4710) Intel Xeon 6700/6500 series processors with P-cores or 6700 series processors with E-cores
-----	---

Core Count	P-cores: Up to 86C/172T; Up to 336MB Cache per CPU E-cores: Up to 144C/144T; Up to 108MB Cache per CPU
Note	Supports up to 350W TDP CPUs (Air Cooled)* Supports up to 350W TDP CPUs (Liquid Cooled) *Air Cooled CPUs with TDP over 250W only supported under specific conditions. Contact a Supermicro representative for details.

GPU

Max GPU Count	Up to 1 double-width or 3 single-width GPUs
Supported GPU	NVIDIA PCIe: A1000, L4, NVIDIA RTX PRO 4500 Blackwell Server Edition, RTX 2000 Ada, RTX 4000 Ada Generation View GPU Options

SYSTEM MEMORY

Memory	Slot Count: 32 DIMM slots Max Memory (1DPC): Up to 4TB 6400MT/s ECC DDR5 RDIMM Max Memory (1DPC): Up to 1TB 8000MT/s ECC DDR5 MRDIMM (P-core only) Max Memory (2DPC): Up to 8TB 6000MT/s ECC DDR5 RDIMM View Memory Options
Memory Voltage	1.1V

ON-BOARD DEVICES

NVMe	NVMe; RAID 0/1/5/10 support(Intel VROC RAID key required) View NVMe Options
Network Connectivity	Via AIOM View AIOM Options View AOC Options

INPUT / OUTPUT

LAN	1 RJ45 1 GbE Dedicated BMC LAN port
USB	2 USB 3.2 Gen1 ports (Rear) 1 USB 3.2 Gen1 port (Front)
Video	1 VGA port

SYSTEM BIOS

BIOS Type	AMI 64MB SPI Flash
-----------	--------------------

MANAGEMENT

Software	SuperCloud Composer (SCC) Supermicro Server Manager (SSM) Super Diagnostics Offline (SDO) Supermicro Thin-Agent Service (TAS) SuperServer Automation Assistant (SAA) New!
Power configurations	Power-on mode for AC power recovery ACPI Power Management

SECURITY

Hardware	Trusted Platform Module (TPM) 2.0 Silicon Root of Trust (RoT) – NIST 800-193 Compliant
----------	---

Features	Cryptographically Signed Firmware Secure Boot Secure Firmware Updates Automatic Firmware Recovery Supply Chain Security: Remote Attestation Runtime BMC Protections System Lockdown
----------	---

PC HEALTH MONITORING

CPU	Monitors for CPU Cores, Chipset Voltages, Memory
Fan	Fans with tachometer monitoring Pulse Width Modulated (PWM) fan connectors Status monitor for speed control
Temperature	Monitoring for CPU and chassis environment Thermal Control for fan connectors

CERTIFICATIONS

Operating Systems	ESXi 8.0 U3, ESXi 9.0, Oracle Linux 9.4, RHEL 9.4, RHEL 10.0, SAP HANA 2.0, Windows Server 2022, Windows Server 2025 View all OS Compatibility and Certification Matrix
Enterprise Solutions	SAP HANA

CHASSIS

Form Factor	1U Rackmount
Model	CSE-HS119-R000NP2

DIMENSIONS AND WEIGHT

Height	1.71" (43.6 mm)
Width	17.3" (438.4 mm)
Depth	29.27" (743.38 mm)
Package	7.99" (H) x 23.81" (W) x 37.4" (D)
Weight	Gross Weight: 41 lbs (18.6 kg) Net Weight: 18.7 lbs (8.5 kg)
Available Color	Silver

FRONT PANEL

Buttons	Power On/Off UID button
LED	HDD activity LAN1 activity Power System information

EXPANSION SLOTS

PCI-Express (PCIe) Configuration	Default 1 PCIe 5.0 x16 FHHL slot 2 PCIe 5.0 x16 FH/10.5"L slots 1 PCIe 5.0 x16 AIOM slot (OCP 3.0 compatible) View AOC Options
----------------------------------	--

DRIVE BAYS / STORAGE

Drive Bays Configuration	Default: Total 8 bays 8 front hot-swap 2.5" NVMe*/SAS*/SATA* drive bays Option A: Total 12 bays 12 front hot-swap 2.5" NVMe*/SAS*/SATA* drive bays (*NVMe/SAS/SATA support may require additional storage controller and/or cables, please see the optional parts list for details) View NVMe Options
M.2	2 M.2 PCIe 5.0 x2 NVMe slots (M-key 2280/22110) View M.2 Options

SYSTEM COOLING

Fans	Up to 8 counter-rotating 40x40x56mm Fan(s)
Air Shroud	2 Air Shrouds
Liquid Cooling	Direct to Chip (D2C) Cold Plate (optional)

POWER SUPPLY

2x 1200W
2x 2000W
2x 1600W
2x 2600W
2x 1200W
2x 1200W Redundant (1 + 1) Titanium Level (96%) Hot-plug power supplies
Dimension (WxHxL)
73.5 x 40 x 265 mm

OPERATING ENVIRONMENT

Environmental Spec.	Name: A2 Operating Temperature: 10°C to 35°C (50°F to 95°F) Non-operating Temperature: -30°C to 60°C (-40°F to 140°F) Operating Relative Humidity: 8% to 80% (max 21° DP; non-condensing) Non-operating Relative Humidity: 8% to 90% (max 38° DP; non-condensing)
---------------------	---

ENVIRONMENTAL / RECYCLING

Recycle	Return Server-End of Life Product
---------	-----------------------------------

06 Built, tested & supported by ServerInvest

Engineered configuration

Every option validated for socket, memory channels, PCIe lanes, power and cooling.

48-hour burn-in

Assembled, firmware-updated and stress-tested before it leaves our workshop.

3-year warranty

Standard on every system, with on-site next-business-day upgrades available.

Rack-ready delivery

Rails, cable management and labelling included — delivered across Europe.



Ready to order or need changes?

Configure this system online or talk to a solutions engineer — we reply within one business day.

office@serverinvest.com

Official manufacturer datasheet: serverinvest.com/product/sys-122h-tn/datasheet/manufacture

