

TECHNICAL DATASHEET

SUPERMICRO • MULTI-NODE & TWIN

Supermicro 2U Twin Server SYS-620TP-HC8TR

2U 4-node TwinPro with 3 3.5" SAS/SATA drives per node and dual 10GbE

SKU SYS-620TP-HC8TR

2U

LGA4189

Supermicro



FORM FACTOR

2U

MAX POWER (BASE)

549 W

HEAT OUTPUT

1,873 BTU/h

PRICE

On request

REQUEST A QUOTATION ONLINE

serverinvest.com/product/sys-620tp-hc8tr

01 Product overview

The Supermicro SYS-620TP-HC8TR is a 2U Twin Server built on dual Intel Xeon Scalable 3rd Gen processors with up to 4 TB of memory in 16 DIMM slots.

2U 4-node TwinPro with 3 3.5" SAS/SATA drives per node and dual 10GbE.


ServerInvest configures every SYS-620TP-HC8TR to order, updates BIOS and BMC firmware, installs your operating system on request and runs a 48-hour burn-in test before delivery. Every system includes a 3-year warranty.

HIGHLIGHTS

- Dual Intel Xeon Scalable 3rd Gen
- Up to 4 TB memory · 16 DIMM slots
- Total 3 bays 3 front hot-swap 3.5" SATA drive bays
- Power: 1x 2200W
- Networking: 2 RJ45 10GBASE-T with Intel X710-AT2

KEY SPECIFICATIONS


Form factor	2U
Processor	2× Intel Xeon Scalable 3rd Gen
Socket	LGA4189
Memory	16 DIMM slots, up to 4 TB
Drive bays	3
Power supply	1× 2200 W
Typical power draw	750 W
Networking	2 RJ45 10GBASE-T with Intel X710-AT2
Dimensions (W×H×D)	437 × 89 mm



02 Power & thermal

Calculated for the base configuration

IDLE	TYPICAL	MAXIMUM	HEAT (MAX)	COOLING	PSU LOAD
119 W	337 W	549 W	1,873 BTU/h	0.5 kW	25%



Typical 337 W · max 549 W · single PSU rating 2200 W


Annual IT energy (24/7)	2,379 kWh
Annual facility energy (PUE 1.5)	3,569 kWh
Annual energy cost	€476 IT · €714 incl. cooling (at 0.20 €/kWh)
CO ₂ emissions / year	0.93 t (grid factor 0.26 kg/kWh)
Power supplies	1× 2200 W

POWER BY COMPONENT	IDLE	TYPICAL	MAX
Chassis, motherboard, fans, BMC	50 W	77 W	110 W
2× CPU (base configuration)	50 W	220 W	370 W
4× Memory (base configuration)	12 W	20 W	36 W

DC loads converted to wall power at 94% PSU efficiency; typical load assumed 70% of the time. Engineering estimates — confirm with the manufacturer's power calculator for critical designs.

03 Power connection diagram

Dual-feed (A/B) connection for redundant power supplies



- Connect PSU 1 to PDU-A and PSU 2 to PDU-B (independent feeds) using IEC C19/C20 (16 A) power cords.
- Maximum current per feed: 2.5 A at 230 V — each feed must be able to carry the full load if the other fails.
- Recommended protection per PDU circuit: MCB 6 A, curve C; RCD according to local regulations.
- Heat to remove at full load: 549 W = 1,873 BTU/h (0.5 kW).

04 Full specifications

MOTHERBOARD

Super X12DPT-PT6

PROCESSOR (PER NODE)

CPU	Dual Socket P+ (LGA-4189) 3rd Gen Intel Xeon Scalable processors
Core Count	Up to 32C/64T; Up to 48MB Cache per CPU
Note	Supports up to 185W TDP CPUs (Air Cooled)

SYSTEM MEMORY (PER NODE)

Memory	Slot Count: 16 DIMM slots Max Memory (2DPC): Up to 4TB 3200MT/s ECC DDR4 RDIMM View Memory Options
Memory Voltage	1.2V

ON-BOARD DEVICES (PER NODE)

Network Connectivity	2 RJ45 10GBASE-T with Intel X710-AT2 View AOC Options
BMC	ASPEED AST2600 BMC

INPUT / OUTPUT (PER NODE)

LAN	1 RJ45 1 GbE Dedicated BMC LAN port
USB	2 USB 3.0 ports (rear)
Video	1 VGA port

SYSTEM BIOS

BIOS Type	AMI 32MB SPI Flash EEPROM
-----------	---------------------------

MANAGEMENT

Software	SuperCloud Composer (SCC) Supermicro Server Manager (SSM) Supermicro Update Manager (SUM) Supermicro SuperDoctor 5 (SD5) Super Diagnostics Offline (SDO) Supermicro Thin-Agent Service (TAS) SuperServer Automation Assistant (SAA) New!
----------	--

Power configurations	Power-on mode for AC power recovery ACPI Power Management ACPI/APM Power Management
----------------------	---

SECURITY

Hardware	Trusted Platform Module (TPM) 2.0 Silicon Root of Trust (RoT) – NIST 800-193 Compliant
----------	---

Features	Cryptographically Signed Firmware Secure Boot Secure Firmware Updates Automatic Firmware Recovery System Lockdown
----------	---

PC HEALTH MONITORING

CPU	5 Phase-switching voltage regulator Monitors for CPU Cores, Chipset Voltages, Memory
-----	---

Fan	Fans with tachometer monitoring Pulse Width Modulated (PWM) fan connectors Status monitor for speed control
-----	---

Temperature	Monitoring for CPU and chassis environment Thermal Control for fan connectors
-------------	--

CERTIFICATIONS

Operating Systems	Oracle Linux 8.3, RHEL 8.3, SLES 12 SP5, SLES 15 SP3, SLES 15 SP4, Windows Server 2019, Windows Server 2022 View all OS Compatibility and Certification Matrix
-------------------	--

CHASSIS

Form Factor	2U Rackmount
-------------	--------------

Model	CSV-827HQ+-R2K20BP4
-------	---------------------

DIMENSIONS AND WEIGHT

Height	3.47" (88 mm)
Width	17.25" (438 mm)
Depth	30.5" (774 mm)
Package	10" (H) x 24.5" (W) x 45" (D)
Weight	Gross Weight: 90 lbs (40.9 kg) Net Weight: 72 lbs (32.7 kg)

Available Color	Black front & silver body
-----------------	---------------------------

FRONT PANEL

Buttons	Power On/Off button UID button
LED	Network activity LED Power status LED System information (overheat/UID) LED

EXPANSION SLOTS (PER NODE)

PCI-Express (PCIe) Configuration	Default 1 PCIe 4.0 x16 LP slot View AOC Options
----------------------------------	---

DRIVE BAYS / STORAGE (PER NODE)

Drive Bays Configuration	Default: Total 3 bays 3 front hot-swap 3.5" SATA drive bays View Drive Options
--------------------------	---

SYSTEM COOLING

Fans	Up to 4x 8cm heavy duty fans with optimal fan speed control
Air Shroud	4 Air Shrouds

POWER SUPPLY

1x 2200W
1x 2200W Redundant Titanium Level (96%) power supply
Dimension (WxHxL)
76 x 40 x 336 mm

OPERATING ENVIRONMENT

Environmental Spec.	Operating Temperature: 10°C to 35°C (50°F to 95°F) Non-operating Temperature: -40°C to 60°C (-40°F to 140°F) Operating Relative Humidity: 8% to 90% (non-condensing) Non-operating Relative Humidity: 5% to 95% (non-condensing)
---------------------	---

05 Built, tested & supported by ServerInvest

Engineered configuration

Every option validated for socket, memory channels, PCIe lanes, power and cooling.

48-hour burn-in

Assembled, firmware-updated and stress-tested before it leaves our workshop.

3-year warranty

Standard on every system, with on-site next-business-day upgrades available.

Rack-ready delivery

Rails, cable management and labelling included — delivered across Europe.



Interested in this solution?

Request a quotation online or talk to a solutions engineer — we reply within one business day.
office@serverinvest.com

Official manufacturer datasheet: serverinvest.com/product/sys-620tp-hc8tr/datasheet/manufacturer

