

TECHNICAL DATASHEET

SUPERMICRO · MULTI-NODE & TWIN

Supermicro 4U FatTwin Server SYS-F620P3-RTBN

4U 4-node FatTwin with 8 3.5" SAS/SATA (optional 6 NVMe) per node

SKU SYS-F620P3-RTBN

4U

LGA4189

Supermicro



FORM FACTOR

4U

MAX POWER (BASE)

602 W

HEAT OUTPUT

2,054 BTU/h

PRICE

On request



REQUEST A QUOTATION ONLINE

serverinvest.com/product/sys-f620p3-rtbn

01 Product overview

The Supermicro SYS-F620P3-RTBN is a 4U FatTwin Server built on dual Intel Xeon Scalable 3rd Gen processors with up to 2 TB of memory in 16 DIMM slots.

4U 4-node FatTwin with 8 3.5" SAS/SATA (optional 6 NVMe) per node.

The chassis accepts up to 1 GPU accelerators for AI, rendering and HPC workloads.


ServerInvest configures every SYS-F620P3-RTBN to order, updates BIOS and BMC firmware, installs your operating system on request and runs a 48-hour burn-in test before delivery. Every system includes a 3-year warranty.

HIGHLIGHTS

- Dual Intel Xeon Scalable 3rd Gen
- Up to 2 TB memory · 16 DIMM slots
- Total 8 bays 6 front hot-swap 3.5" NVMe/SAS/SATA drive bays
- Up to 1 GPUs
- Power: 1x 2200W
- Networking: 1 RJ45 1GbE

KEY SPECIFICATIONS


Form factor	4U
Processor	2× Intel Xeon Scalable 3rd Gen
Socket	LGA4189
Memory	16 DIMM slots, up to 2 TB
Drive bays	10 (10 NVMe)
GPU	Up to 1 GPUs
Power supply	1× 2200 W
Typical power draw	1200 W
Networking	1 RJ45 1GbE
Dimensions (W×H×D)	437 × 178 mm



02 Power & thermal

Calculated for the base configuration

IDLE	TYPICAL	MAXIMUM	HEAT (MAX)	COOLING	PSU LOAD
143 W	374 W	602 W	2,054 BTU/h	0.6 kW	27%



Typical 374 W · max 602 W · single PSU rating 2200 W


Annual IT energy (24/7)	2,669 kWh
Annual facility energy (PUE 1.5)	4,004 kWh
Annual energy cost	€534 IT · €801 incl. cooling (at 0.20 €/kWh)
CO ₂ emissions / year	1.04 t (grid factor 0.26 kg/kWh)
Power supplies	1× 2200 W

POWER BY COMPONENT	IDLE	TYPICAL	MAX
Chassis, motherboard, fans, BMC	72 W	112 W	160 W
2× CPU (base configuration)	50 W	220 W	370 W
4× Memory (base configuration)	12 W	20 W	36 W

DC loads converted to wall power at 94% PSU efficiency; typical load assumed 70% of the time. Engineering estimates — confirm with the manufacturer's power calculator for critical designs.

03 Power connection diagram

Dual-feed (A/B) connection for redundant power supplies



- Connect PSU 1 to PDU-A and PSU 2 to PDU-B (independent feeds) using IEC C19/C20 (16 A) power cords.
- Maximum current per feed: 2.8 A at 230 V — each feed must be able to carry the full load if the other fails.
- Recommended protection per PDU circuit: MCB 6 A, curve C; RCD according to local regulations.
- Heat to remove at full load: 602 W = 2,054 BTU/h (0.6 kW).

04 Full specifications

MOTHERBOARD

Super X12DPFR-AN6

PROCESSOR (PER NODE)

CPU	Dual Socket P+ (LGA-4189) 3rd Gen Intel Xeon Scalable processors
Core Count	Up to 36C/72T; Up to 54MB Cache per CPU
Note	Supports up to 205W TDP CPUs (Air Cooled)

GPU (PER NODE)

Max GPU Count	Up to 1 double-width GPU
---------------	--------------------------

SYSTEM MEMORY (PER NODE)

Memory	Slot Count: 16 DIMM slots Max Memory (2DPC): Up to 2TB non-ECC Supports Intel Optane persistent memory 200 series View Memory Options
--------	--

ON-BOARD DEVICES (PER NODE)

Network Connectivity	1 RJ45 1GbE View AIOM Options View AOC Options
----------------------	--

INPUT / OUTPUT (PER NODE)

LAN	1 RJ45 1 GbE Dedicated BMC LAN port
USB	2 USB 3.0 ports (rear)
Video	1 VGA port

SYSTEM BIOS

BIOS Type	AMI 32MB SPI FLASH ROM
-----------	------------------------

MANAGEMENT

Software	SuperCloud Composer (SCC) Supermicro Server Manager (SSM) Supermicro Update Manager (SUM) Supermicro SuperDoctor 5 (SD5) Super Diagnostics Offline (SDO) Supermicro Thin-Agent Service (TAS) SuperServer Automation Assistant (SAA) New!
----------	--

Power configurations	ACPI/APM Power Management
----------------------	---------------------------

SECURITY

Hardware	Trusted Platform Module (TPM) 2.0 Silicon Root of Trust (RoT) – NIST 800-193 Compliant
----------	---

Features	Cryptographically Signed Firmware Secure Boot Secure Firmware Updates Automatic Firmware Recovery System Lockdown
----------	---

PC HEALTH MONITORING

CPU	4+1 Phase-switching voltage regulator Monitors for CPU Cores, Chipset Voltages, Memory.
-----	--

Fan	Fans with tachometer monitoring Pulse Width Modulated (PWM) fan connectors Status monitor for speed control
-----	---

Temperature	Monitoring for CPU and chassis environment
-------------	--

CERTIFICATIONS

Operating Systems	RHEL 9.0, SLES 12 SP5, SLES 15 SP2 View all OS Compatibility and Certification Matrix
-------------------	--

CHASSIS

Form Factor	4U Rackmount
-------------	--------------

Model	CSE-F424AS3-R2K20BP
-------	---------------------

DIMENSIONS AND WEIGHT

Height	6.96" (177 mm)
Width	17.63" (448 mm)
Depth	29" (737 mm)
Package	15" (H) x 28.3" (W) x 42.4" (D)
Weight	Gross Weight: 200 lbs (90.71 kg) Net Weight: 150 lbs (68.04 kg)
Available Color	Silver

FRONT PANEL

Buttons	Power On/Off button UID button
LED	HDD activity LED Network activity LEDs Power status LED Universal Information (UID) LED

EXPANSION SLOTS (PER NODE)

PCI-Express (PCIe) Configuration	Default 1 PCIe 4.0 x16 LP slot 1 PCIe 4.0 x16 AIOM slot (OCP 3.0 compatible) View AOC Options
----------------------------------	--

DRIVE BAYS / STORAGE (PER NODE)

Drive Bays Configuration	Default: Total 8 bays 6 front hot-swap 3.5" NVMe/SAS/SATA drive bays 2 rear hot-swap 3.5" NVMe/SAS/SATA drive bays View NVMe Options View Drive Options
--------------------------	--

SYSTEM COOLING

Fans	Up to 2x 8cm Fan(s)
Air Shroud	1 Air Shroud

POWER SUPPLY

1x 2200W
1x 2200W Redundant Titanium Level (96%) power supply
Dimension (WxHxL)
76 x 40 x 336 mm

05 Built, tested & supported by ServerInvest

Engineered configuration

Every option validated for socket, memory channels, PCIe lanes, power and cooling.

48-hour burn-in

Assembled, firmware-updated and stress-tested before it leaves our workshop.

3-year warranty

Standard on every system, with on-site next-business-day upgrades available.

Rack-ready delivery

Rails, cable management and labelling included — delivered across Europe.



Interested in this solution?

Request a quotation online or talk to a solutions engineer — we reply within one business day.
office@serverinvest.com

Official manufacturer datasheet: serverinvest.com/product/sys-f620p3-rtbn/datasheet/manufacture

