

TECHNICAL DATASHEET

TECHLY • SERVER RACKS

Techly I-CASE EE-2008BK6 8U 600 mm × 600 mm wall- or floor-mount 19-inch rack cabinet, perforated steel door, black

8U 19-inch wall- or floor-mount cabinet, 600 × 600 × 435 mm

SKU I-CASE EE-2008BK6

8U

Techly



HEIGHT IN U

8U

EXTERNAL DIMENSIONS

435 × 600 × 600 mm

MANUFACTURER

Techly

PRICE

On request**REQUEST A QUOTATION ONLINE**serverinvest.com/product/techly-i-case-ee-2008bk6

01 Product overview

The Techly I-CASE EE-2008BK6 is an 8U 19-inch wall- or floor-mount cabinet from the I-CASE range, measuring 435 mm high, 600 mm wide and 600 mm deep, in black. It is aimed at photovoltaic battery storage systems and other energy equipment that needs a ventilated 19-inch enclosure, installable on the wall or the floor.

Access is through a perforated steel front door (75% open area) that can be reversed and opens up to 210°, secured by a key lock. The side panels are removable and lockable. The rear is closed by a solid panel. The 19-inch mounting profiles are depth-adjustable, with up to 460 mm of usable depth.

Cable entry points allow tidy routing of power and data cabling. Adjustable feet allow the cabinet to be levelled. The enclosure is rated IP20. It is delivered pre-assembled. A grounding kit is included.

Certifications listed for this model include CE, ISO 9001, EN 60529, EN 62208, EN12150, IEC 297, IEC 297-1, IEC 297-2, IEC 297-3.

HIGHLIGHTS

- 8U 19-inch wall- or floor-mount cabinet, 600 × 600 × 435 mm
- Perforated steel front door (75% open area), reversible, lockable
- Removable side panels with locks
- IP20 protection

KEY SPECIFICATIONS

Manufacturer	Techly
Model	I-CASE EE-2008BK6
Series	I-CASE energy-storage rack cabinet
Rack type	Wall-mount cabinet
Height in U	8U
Rack standard	19-inch
External dimensions (H × W × D)	435 × 600 × 600 mm
Usable depth	460 mm
Weight	20.853 kg
Front mounting profiles	Adjustable
Rear mounting profiles	Fixed
Front door	Perforated steel front door (75% open area), reversible, opening 210°



02 Full specifications

GENERAL

Manufacturer	Techly
Model	I-CASE EE-2008BK6
Series	I-CASE energy-storage rack cabinet
Rack type	Wall-mount cabinet

DIMENSIONS

Height in U	8U
Rack standard	19-inch
External dimensions (H × W × D)	435 × 600 × 600 mm
Usable depth	460 mm
Weight	20.853 kg

MOUNTING

Front mounting profiles	Adjustable
Rear mounting profiles	Fixed

DOORS & PANELS

Front door	Perforated steel front door (75% open area), reversible, opening 210°
Rear	Solid
Side panels	Removable, lockable
Lock	Key lock

COOLING

Cooling	Passive
---------	---------

CONSTRUCTION

Colour	Black
Cable entry	Yes
Levelling feet	Yes
Grounding kit	Included
Assembly	Pre-assembled

COMPLIANCE

IP rating	IP20
Certifications	CE, ISO 9001, EN 60529, EN 62208, EN12150, IEC 297, IEC 297-1, IEC 297-2, IEC 297-3

WARRANTY

Warranty	1-year
----------	--------

03 Engineered, delivered & supported by ServerInvest

Engineering & sizing

Selected and sized against your real IT load, room and redundancy targets.

Installation

Delivery, installation and commissioning by our engineers across Europe.

Certified processes

ISO 9001, ISO 14001 and ISO 27001 certified project delivery.

Service & support

Maintenance, spare parts and support from a single partner.



Interested in this solution?

Request a quotation online or talk to a solutions engineer — we reply within one business day.
office@serverinvest.com

