

TECHNICAL DATASHEET

TECHLY • SERVER RACKS

Techly I-CASE EN-4288B 42U 800 mm × 800 mm floor-standing 19-inch rack cabinet, tempered-glass door, black

42U 19-inch floor-standing cabinet, 800 × 800 × 2004 mm, 500 kg load

SKU I-CASE EN-4288B

42U

Techly



HEIGHT IN U

42U

EXTERNAL DIMENSIONS

**2004 × 800 × 800
mm**

MANUFACTURER

Techly

PRICE

On request**REQUEST A QUOTATION ONLINE**serverinvest.com/product/techly-i-case-en-4288b

01 Product overview

The Techly I-CASE EN-4288B is a 42U 19-inch floor-standing cabinet from the I-CASE range, measuring 2004 mm high, 800 mm wide and 800 mm deep, in black. It is aimed at server rooms, network rooms and offices that need a full-height enclosure for servers, switches and patching.

Access is through a tempered-glass front door that can be reversed, secured by a key lock. The side panels are removable and lockable. The rear is closed by a solid panel. The 19-inch mounting profiles are depth-adjustable.

Cable entry points allow tidy routing of power and data cabling. Adjustable feet allow the cabinet to be levelled. The enclosure is rated IP20. Techly specifies a maximum load of 500 kg. It is delivered pre-assembled. A grounding kit is included.

HIGHLIGHTS

- 42U 19-inch floor-standing cabinet, 800 × 800 × 2004 mm
- Tempered-glass front door, reversible, lockable
- Removable side panels with locks
- IP20 protection
- Maximum load 500 kg

KEY SPECIFICATIONS

Manufacturer	Techly
Model	I-CASE EN-4288B
Series	I-CASE floor-standing cabinet
Rack type	Floor-standing cabinet
Height in U	42U
Rack standard	19-inch
External dimensions (H × W × D)	2004 × 800 × 800 mm
Weight	113.925 kg
Front mounting profiles	Adjustable
Rear mounting profiles	Adjustable
Front door	Tempered-glass front door, reversible
Rear	Solid



02 Full specifications

GENERAL

Manufacturer	Techly
Model	I-CASE EN-4288B
Series	I-CASE floor-standing cabinet
Rack type	Floor-standing cabinet

DIMENSIONS

Height in U	42U
Rack standard	19-inch
External dimensions (H × W × D)	2004 × 800 × 800 mm
Weight	113.925 kg

MOUNTING

Front mounting profiles	Adjustable
Rear mounting profiles	Adjustable

DOORS & PANELS

Front door	Tempered-glass front door, reversible
Rear	Solid
Side panels	Removable, lockable
Lock	Key lock

LOAD

Static load	500 kg
-------------	--------

CONSTRUCTION

Colour	Black
Cable entry	Yes
Levelling feet	Yes
Grounding kit	Included
Assembly	Pre-assembled

COMPLIANCE

IP rating	IP20
-----------	------

WARRANTY

Warranty	1-year
----------	--------

03 Engineered, delivered & supported by ServerInvest

Engineering & sizing

Selected and sized against your real IT load, room and redundancy targets.

Installation

Delivery, installation and commissioning by our engineers across Europe.

Certified processes

ISO 9001, ISO 14001 and ISO 27001 certified project delivery.

Service & support

Maintenance, spare parts and support from a single partner.



Interested in this solution?

Request a quotation online or talk to a solutions engineer — we reply within one business day.
office@serverinvest.com

