

TECHNICAL DATASHEET

TECHLY • SERVER RACKS

Techly I-CASE EW-26822BK 22U 600 mm × 800 mm wall-mount 19-inch rack cabinet, tempered-glass door, black

22U 19-inch wall-mount cabinet, 600 × 800 × 1057 mm, 105 kg load

SKU I-CASE EW-26822BK

22U

Techly



HEIGHT IN U

22U

EXTERNAL DIMENSIONS

**1057 × 600 × 800
mm**

MANUFACTURER

Techly

PRICE

On request**REQUEST A QUOTATION ONLINE**serverinvest.com/product/techly-i-case-ew-26822bk

01 Product overview

The Techly I-CASE EW-26822BK is a 22U 19-inch wall-mount cabinet from the I-CASE range, measuring 1057 mm high, 600 mm wide and 800 mm deep, in black. It is aimed at offices, small network rooms and technical spaces that need a compact, lockable enclosure for switches, patch panels and small network equipment.

Access is through a tempered-glass front door, secured by a key lock. The side panels are removable. The rear is closed by a solid panel. The 19-inch mounting profiles are depth-adjustable.

The enclosure is rated IP20 and IK09 for impact resistance. Techly specifies a maximum load of 105 kg. It is delivered pre-assembled.

Certifications listed for this model include EC, ISO 9001:2015, EN 60529, EN 61439, EN 62208, EN12150, IEC 297 , IEC 297-1 , IEC 297-2, IEC 297-3.

HIGHLIGHTS

- 22U 19-inch wall-mount cabinet, 600 × 800 × 1057 mm
- Tempered-glass front door, lockable
- Removable side panels
- IP20 protection, IK09
- Maximum load 105 kg

KEY SPECIFICATIONS

Manufacturer	Techly
Model	I-CASE EW-26822BK
Series	I-CASE wall cabinet
Rack type	Wall-mount cabinet
Height in U	22U
Rack standard	19-inch
External dimensions (H × W × D)	1057 × 600 × 800 mm
Weight	42 kg
Front mounting profiles	Adjustable
Rear mounting profiles	Fixed
Front door	Tempered-glass front door
Rear	Solid



02 Full specifications

GENERAL

Manufacturer	Techly
Model	I-CASE EW-26822BK
Series	I-CASE wall cabinet
Rack type	Wall-mount cabinet

DIMENSIONS

Height in U	22U
Rack standard	19-inch
External dimensions (H × W × D)	1057 × 600 × 800 mm
Weight	42 kg

MOUNTING

Front mounting profiles	Adjustable
Rear mounting profiles	Fixed

DOORS & PANELS

Front door	Tempered-glass front door
Rear	Solid
Side panels	Removable
Lock	Key lock

LOAD

Static load	105 kg
-------------	--------

CONSTRUCTION

Colour	Black
Assembly	Pre-assembled

COMPLIANCE

IP rating	IP20
IK rating	IK09
Certifications	EC, ISO 9001:2015, EN 60529, EN 61439, EN 62208, EN12150, IEC 297 , IEC 297-1 , IEC 297-2, IEC 297-3

03 Engineered, delivered & supported by ServerInvest

Engineering & sizing

Selected and sized against your real IT load, room and redundancy targets.

Installation

Delivery, installation and commissioning by our engineers across Europe.

Certified processes

ISO 9001, ISO 14001 and ISO 27001 certified project delivery.

Service & support

Maintenance, spare parts and support from a single partner.



Interested in this solution?

Request a quotation online or talk to a solutions engineer — we reply within one business day.
office@serverinvest.com

