

TECHNICAL DATASHEET

TECHLY • SERVER RACKS

Techly I-CASE FP-4512G 12U 570 mm × 450 mm wall-mount 19-inch rack cabinet, tempered-glass door, grey

12U 19-inch wall-mount cabinet, 570 × 450 × 635 mm, 60 kg load

SKU I-CASE FP-4512G

12U

Techly



HEIGHT IN U

12U

EXTERNAL DIMENSIONS

635 × 570 × 450 mm

MANUFACTURER

Techly

PRICE

On request**REQUEST A QUOTATION ONLINE**serverinvest.com/product/techly-i-case-fp-4512g

01 Product overview

The Techly I-CASE FP-4512G is a 12U 19-inch wall-mount cabinet from the I-CASE range, measuring 635 mm high, 570 mm wide and 450 mm deep, in grey. It is aimed at offices and small network rooms, shipped flat-packed for economical transport.

Access is through a tempered-glass front door that can be reversed and opens up to 180°, secured by a key lock. The side panels are removable and lockable. The rear is closed by a solid panel.

The enclosure is rated IP20. Techly specifies a maximum load of 60 kg. It is supplied as a flat pack for quick assembly.

HIGHLIGHTS

- 12U 19-inch wall-mount cabinet, 570 × 450 × 635 mm
- Tempered-glass front door, reversible, lockable
- Removable side panels with locks
- IP20 protection
- Maximum load 60 kg

KEY SPECIFICATIONS

Manufacturer	Techly
Model	I-CASE FP-4512G
Series	I-CASE flat-pack wall cabinet
Rack type	Wall-mount cabinet
Height in U	12U
Rack standard	19-inch
External dimensions (H × W × D)	635 × 570 × 450 mm
Usable depth	425 mm
Weight	21 kg
Front door	Tempered-glass front door, reversible, opening 180°
Rear	Solid
Side panels	Removable, lockable



02 Full specifications

GENERAL

Manufacturer	Techly
Model	I-CASE FP-4512G
Series	I-CASE flat-pack wall cabinet
Rack type	Wall-mount cabinet

DIMENSIONS

Height in U	12U
Rack standard	19-inch
External dimensions (H × W × D)	635 × 570 × 450 mm
Usable depth	425 mm
Weight	21 kg

DOORS & PANELS

Front door	Tempered-glass front door, reversible, opening 180°
------------	---

Rear	Solid
Side panels	Removable, lockable
Lock	Key lock

LOAD

Static load	60 kg
-------------	-------

COOLING

Cooling	Active
---------	--------

CONSTRUCTION

Colour	Grey
Assembly	Flat-pack

COMPLIANCE

IP rating	IP20
-----------	------

03 Engineered, delivered & supported by ServerInvest

Engineering & sizing

Selected and sized against your real IT load, room and redundancy targets.

Installation

Delivery, installation and commissioning by our engineers across Europe.

Certified processes

ISO 9001, ISO 14001 and ISO 27001 certified project delivery.

Service & support

Maintenance, spare parts and support from a single partner.



Interested in this solution?

Request a quotation online or talk to a solutions engineer — we reply within one business day.
office@serverinvest.com

