

TECHNICAL DATASHEET

TECHLY • SERVER RACKS

Techly I-CASE SVR-I1210BK 12U 600 mm × 1000 mm floor-standing server 19-inch rack cabinet, glass door, black

12U 19-inch floor-standing server cabinet, 600 × 1000 × 670 mm, 360 kg load

SKU I-CASE SVR-I1210BK

12U

Techly



HEIGHT IN U

12U

EXTERNAL DIMENSIONS

**670 × 600 × 1000
mm**

MANUFACTURER

Techly

PRICE

On request**REQUEST A QUOTATION ONLINE**serverinvest.com/product/techly-i-case-svr-i1210bk

01 Product overview

The Techly I-CASE SVR-I1210BK is a 12U 19-inch floor-standing server cabinet from the I-CASE range, measuring 670 mm high, 600 mm wide and 1000 mm deep, in black. It is aimed at offices and small businesses that want a lockable server cabinet able to sit under or beside a desk.

Access is through a glass front door that can be reversed. The side panels are removable. The rear is closed by a solid panel. The 19-inch mounting profiles are depth-adjustable, with up to 940 mm of usable depth.

Cable entry points allow tidy routing of power and data cabling. Castors and adjustable feet make it easy to move and level the cabinet. The enclosure is rated IP20. Techly specifies a maximum load of 360 kg (225 kg when rolling). It is delivered pre-assembled.

Certifications listed for this model include CE, ISO 9001, EN 60529, EN 62208, EN12150, IEC 297, IEC 297-1, IEC 297-2, IEC 297-3.

HIGHLIGHTS

- 12U 19-inch floor-standing server cabinet, 600 × 1000 × 670 mm
- Glass front door, reversible
- Removable side panels
- IP20 protection
- Maximum load 360 kg

KEY SPECIFICATIONS

Manufacturer	Techly
Model	I-CASE SVR-I1210BK
Series	I-CASE under-desk server cabinet
Rack type	Under-desk server cabinet
Height in U	12U
Rack standard	19-inch
External dimensions (H × W × D)	670 × 600 × 1000 mm
Usable depth	940 mm
Weight	57.75 kg
Front mounting profiles	Adjustable
Rear mounting profiles	Adjustable
Front door	Glass front door, reversible



02 Full specifications

GENERAL

Manufacturer	Techly
Model	I-CASE SVR-I1210BK
Series	I-CASE under-desk server cabinet
Rack type	Under-desk server cabinet

DIMENSIONS

Height in U	12U
Rack standard	19-inch
External dimensions (H × W × D)	670 × 600 × 1000 mm
Usable depth	940 mm
Weight	57.75 kg

MOUNTING

Front mounting profiles	Adjustable
Rear mounting profiles	Adjustable

DOORS & PANELS

Front door	Glass front door, reversible
Rear	Solid
Side panels	Removable

LOAD

Static load	360 kg
Rolling load	225 kg

CONSTRUCTION

Colour	Black
Cable entry	Yes
Casters	Yes
Levelling feet	Yes
Assembly	Pre-assembled

COMPLIANCE

IP rating	IP20
Certifications	CE, ISO 9001, EN 60529, EN 62208, EN12150, IEC 297, IEC 297-1, IEC 297-2, IEC 297-3

WARRANTY

Warranty	15-year
----------	---------

03 Engineered, delivered & supported by ServerInvest

Engineering & sizing

Selected and sized against your real IT load, room and redundancy targets.

Installation

Delivery, installation and commissioning by our engineers across Europe.

Certified processes

ISO 9001, ISO 14001 and ISO 27001 certified project delivery.

Service & support

Maintenance, spare parts and support from a single partner.



Interested in this solution?

Request a quotation online or talk to a solutions engineer — we reply within one business day.
office@serverinvest.com

